

Item# 3202H00120

- General Specifications
- Audio frequency bandwidth 35 - 20000 Hz
- Signal to Noise 120 dB-A
- THD at 1 kHz 0.3 Prozent
- Operating temperature range -10 to 55 Celsius
- Peak deviation 48 kHz
- Nominal deviation 20 kHz
- Radio Output Power (min/max) 10 to 50 mW
- Transmitter Synchronization Manual
- Mute Switch Type Jack Mono (1/4")
- Mute Switch Gender Female
- Switching bandwidth 30 MHz
- Recommended simultaneous channels 50
- Number of selectable frequencies 1220 (selectable in 25kHz steps)
- Frequency Selection Selectable frequency in 25kHz steps
- Radio range (Line of sight) 100m (depending on antenna system)
- Switchable RF power no
- Modulation FM (Frequency Modulation)
- Encryption No encryption
- Diversity True Diversity
- Pilot Tones yes
- Dimensions

- Length25 mm
- Height91 mm
- Width70 mm
- Design
- Bodymetal
- Finishblack
- Audio Input
- TypeMini XLR
- GenderFemale
- Contacts3-pin
- Maximum audio level12 dB
- Battery
- Battery typeAKG BP 4000
- Compatible Charging SystemCU4000
- Number of batteries1
- Operating time12 h
- Battery 2
- Battery typeHR 6 AA (NiHM) rechargeable
- Compatible Charging SystemCU4000
- Number of batteries2
- Operating time15 h
- Battery 1
- Battery typeLR6 AA alkaline

- Number of batteries 2
- Operating time 15 h