

AKG CK69 Specs

Transducer	Condenser
Polar Pattern	Hypercardioid/Directional
Frequency Response	20 Hz - 18 kHz
Dynamic Range (Typical)	123/129/131 dB, (A-Weighted)
Signal-to-Noise Ratio	83/85/79 dB, (A-Weighted)
Maximum Input Sound Level	134/140/142 dB for 0.5% THD
Power Requirements	Phantom Power, 48v (to DIN 45596)
Output Impedance	150 Ohms
Output Connectors	Screw-On, Proprietary Connector to C480B C480B then Terminates to an XLR-3M Type Connector
Pad	Yes, (0, +6 and -10 db <i>Found on C480B Module</i>)
Low Frequency Roll-Off	Yes, (Switchable Low-Frequency Cuts 150 Hz and 75 Hz at 12dB, <i>Found on C480B Module</i>)

Applications	ENG, Videography, Film, Stage, etc.
--------------	-------------------------------------

Dimensions	6.9/12.5 x .8" (176/317 x 21mm) LxDiameter
------------	---

Weight	6.9" L = 2.5 oz. (70 g) 12.5" L = 17.7 oz. (500 g)
--------	---

Packaging Info

Package Weight	1.29 lb
----------------	---------

Box Dimensions (LxWxH)	22 x 3 x 3"
------------------------	-------------
