

AKG P820 Specs

Microphone

Polar Pattern	Cardioid, Figure-8, Omnidirectional
---------------	-------------------------------------

Pattern Selection	Switched
-------------------	----------

Circuitry	Tube
-----------	------

Pad	-20 dB
-----	--------

High-Pass Filter	80 Hz, 12 dB/Octave
------------------	---------------------

Performance

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	155 dB SPL
-------------	------------

Impedance	200 Ohms
-----------	----------

Load Impedance	1000 Ohms
----------------	-----------

Sensitivity	20 mV/Pa
-------------	----------

Signal-to-Noise Ratio	78 dB A-Weighted
-----------------------	------------------

Equivalent Noise Level	16 dB A-Weighted
------------------------	------------------

Connectivity

Output Connectors	1 x XLR 3-Pin
-------------------	----------------------

Power

Operating Current Consumption	125 mA
-------------------------------	--------

AC Input Power (PSU)	110 to 240 VAC, 50 / 60 Hz
----------------------	----------------------------

Physical

Operating Temperature	22 to 92°F / -10 to 60°C
-----------------------	--------------------------

Dimensions	ø: 2.13 x L: 8.35" / ø: 54 x L: 212 mm
------------	--

Weight	26.98 oz / 765 g
--------	------------------

Packaging Info

Package Weight	12.685 lb
----------------	-----------

Box Dimensions (LxWxH)	16.2 x 12.7 x 6.15"
------------------------	---------------------

