

Denon DJ PRIME GO Specs

Frequency Response	20 Hz to 20 kHz (± 1 dB)
Dynamic Range	> 109 dB (A-Weighted)
Signal-to-Noise Ratio (SNR)	> 92 dB (A-Weighted)
Channel Separation	< -88 dB (1 kHz, Unity)
Headroom	Aux Input: > 15 dB Mic Input: > 20 dB Outputs: > 15 dB
THD	Aux: < 0.01% (1 kHz, Unity) Microphone: < 0.02% (1 kHz, Unity)
Analog Input	Microphone: Unity: -40 dBV (Unity) Minimum: -54 dBV (Minimum) Aux: Minimum: +15 dBV (Maximum) Maximum: 0 dBV (Unity)
Analog Output	Master, Balanced: +18 dBu (Maximum) +4 dBu (Unity) Master, Unbalanced: +15 dBu (Maximum) 0 dBu (Unity) Booth: +18 dBu (Maximum)

+4 dBu (Unity)

Headphone Output: <40 mW

Connections

Analog Outputs:

Master L/R: 2 x XLR (Balanced)

Master L/R: Stereo RCA Pair
(Unbalanced)

Booth L/R: 2 x 1/4" / 6.35 mm TRS
(Balanced)

Headphone: 1 x 1/4" / 6.35 mm TRS

Headphone: 1 x 1/8" / 3.5 mm TRS

Analog Inputs:

Aux: 1 x Stereo RCA (Pair) Line Level

Microphone 1/2: 2 x Combo XLR-1/4"
/ 6.35 mm

Digital:

1 x USB Type-A Port (for USB Drives)

1 x USB Type-B Port (to Computer)

1 x SD-Card Input

1 x Ethernet Port

1 x Power Adapter Input

Power

Connection: DC, Center Positive

Voltage: 19 V 3.42 A

Consumption: 30 W Maximum

Dimensions (W x D x H)

16.2 x 10.8 x 2.1" / 411 x 274 x 53
mm

Weight

8.1 lb / 3.7 kg
