

Denon DJ PRIME 2 Specs

Frequency Response	20 Hz to 20 kHz (± 1 dB)
Dynamic Range	> 112 dB (A-Weighted)
Signal-to-Noise Ratio (SNR)	> 92 dB (A-Weighted)
Channel Separation	< -85 dB (1 kHz, Unity)
Headroom	Aux/Line Input: > 15 dB Mic Input: > 20 dB Outputs: > 20 dB
THD	Aux/Line: < 0.01% (1 kHz, Unity) Microphone: < 0.02% (1 kHz, Unity)
Analog Input	Microphone: Unity: -40 dBu Minimum: -60 dBu Aux/Line: Maximum: +15 dBV Unity: 0 dBV
Analog Output	Master, Balanced: +24 dBu (Maximum) +4 dBu (Unity) Master, Unbalanced: +20 dBu (Maximum) 0 dBu (Unity) Booth: +24 dBu (Maximum)

+4 dBu (Unity)

Headphone Output: <150 mW at 40 Ohms

Connections

Audio Outputs:

Master L/R: 2 x XLR (Balanced)

Master L/R: Stereo RCA Pair (Unbalanced)

Booth L/R: 2 x XLR (Balanced)

Headphone: 1 x 1/4" / 6.35 mm TRS

Headphone: 1 x 1/8" / 3.5 mm TRS

Audio Inputs:

1 x Stereo RCA (Pair) Line Level

Microphone 1/2: 2 x Combo XLR-1/4" / 6.35 mm

Digital:

3 x USB Type-A Ports (for USB Drives, 5 V, 1 A)

1 x USB Type-B Port (to Computer)

1 x SD Card Input

1 x Ethernet Port

1 x IEC Power Cable Input

1 x 2.5" SATA HD Bay

Power

Connection: IEC

Input Voltage: 100 to 240 VAC, 50/60 Hz

Consumption:

34 W (With Smartphone Charging from USB 3 Port)

32 W (Without Smartphone Charging)

Dimensions (W x D x H)

25.4 x 16.2 x 4.7" / 64.5 x 41.0 x 12.0 cm

Weight

15.9 lb / 7.2 kg
