

- **Audio**
    - **Analog Output:** 2.0 Vrms (0 dBFS, 1 kHz)
    - **Dynamic Range:** 116 dB
    - **Distortion (THD+N):** < 0.0015%
    - **Frequency Range:** 22–22,000 Hz
    - **Digital Output:**
      - Sampling Rate: 96 kHz
      - Bit Depth: 24-bit
- 

- **Platter**
    - 8.0" / 203 mm (diameter)
    - Metal construction with display & touch-capacitive circuitry
- 

- **Display**
    - **Main:**
      - 7.0" / 178 mm (diagonal)
      - 6.0" x 3.6" / 152 x 91 mm (width x height)
      - Full-color LED-backlit display with touchinterface
    - **Platter:**
      - 2.2" / 56 mm (diameter)
      - Full-color LED-backlit display
- 

- **Connections**
    - (2) RCA output pairs
    - (2) coaxial digital outputs
    - (1) 1/8" (3.5 mm) mini TS input (remote start)
    - (3) USB Type-A ports (for USB drives) (Rear-panel ports supply 900mA for USB 3.0 devices, 500 mA for USB 2.0 devices. Frontpanelport supplies 500 mA for USB 2.0 devices only.)
    - (1) USB Type-B port (for computer connection)
    - (1) SD card slot
    - (1) Ethernet link port
    - (1) IEC power input
- 

- **Power**
    - **Connection:** IEC
    - **Input Voltage:** 110–240 VAC, 50/60 Hz
    - **Consumption:** 75W
- 

- **Dimensions (width x depth x height)**
  - 320mm X 419mm X 135mm
  - 12.6" x 16.5" x 5.3"

- 32.0 x 41.9 x 13.5 cm
- 

- **Weight (without USB and power cable)**

- 8.79 lbs.
  - 4 kg
- 

- **Supported Media**

- **Type:**

- SD/SDHC card
- USB mass-storage devices (flash memory, external HDD enclosures)

- **File Systems:**

- exFAT
- FAT32 (recommended)

- **File Formats:**

- AAC/M4A
- AIF/AIFF (44.1–192 kHz, 16–32-bit)
- ALAC (44.1 - 192 kHz, 16-32-bit)
- FLAC (44.1 - 192 kHz, 16-24-bit)
- MP3 (32–320 kbps, VBR)
- MP4
- Ogg Vorbis
- WAV (44.1–192 kHz, 16–32-bit)