

- **Audio**
 - **Analog Output:** 2.0 Vrms (0 dBFS, 1 kHz)
 - **Signal-to-Noise Ratio:** 116 dB
 - **Distortion (THD+N):** < 0.0015%
 - **Frequency Range:** 22–22,000 Hz
 - **Digital Output:**
 - Sampling Rate: 96 kHz
 - Bit Depth: 24-bit

- **Platter**
 - **Diameter:** 8.5" / 216mm (diameter)
 - **Material:** Metal construction with display and touch-capacitive circuitry

- **Display**
 - **Main:**
 - 10.1" / 257 mm (diagonal)
 - 10.11" x 6.9" / 257 x 175 mm (width x height)
 - Full-color LED-backlit display with touch interface
 - **Platter:**
 - 2.2" / 56 mm (diagonal)
 - Full-color LED-backlit display

- **Connections**
 - (2) RCA output pairs
 - (2) coaxial digital outputs
 - (1) 1/8" (3.5 mm) mini TS input (remote start)
 - (3) USB Type-A ports (for USB drives) (Rear-panel ports supply 900 mA for USB 3.0 devices, 500 mA for USB 2.0 devices. Front panel port supplies 500 mA for USB 2.0 devices only.)
 - (1) USB Type-B port (for computer connection)
 - (1) SD card slot
 - (1) Ethernet link port
 - (1) IEC power input
 - (1) 2.5" SATA HD bay

- **Power**
 - **Connection:** Locking IEC
 - **Input Voltage:** 110–240 VAC, 50/60 Hz

- **Dimensions (Width x Depth x Height)**
 - 319.5mm X 463.3mm X 151.17mm
 - 12.6" x 18.2" x 6"

- **Weight (Without USB and Power Cable)**

- 12.76 lbs.

- 5.8 kg

- **Supported Media**

- **Type:**

- SD/SDHC card

- USB mass-storage devices (flash memory, external HDD enclosures)

- 2.5" SATA hard drives

- **File Systems:**

- exFAT

- FAT32 (recommended)

- **File Formats:**

- AAC/M4A

- AIF/AIFF (44.1–192 kHz, 16–32-bit)

- ALAC

- FLAC

- MP3 (32–320 kbps)

- MP4

- Ogg Vorbis

- WAV (44.1–192 kHz, 16–32-bit)