

Technical details

| | |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Interface | RS-232 + USB + Keyboard Wedge |
| Programming function | Yes |
| Linear (1D) barcodes supported | Codabar, Code 11, Code 128, Code 39, Code 93, GS1-128 (UCC/EAN-128), MSI, Plessey, U.P.C. |
| 2D (matrix & stacked) barcodes supported | Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39 |
| LED indicators | 1 |
| Colour of product | Black, Green |
| International Protection (IP) code | IP67 |

Power

| | |
|----------------------------|----------------------|
| Battery technology | Lithium-Ion (Li-Ion) |
| Battery capacity | 3100 mAh |
| Number of reads per charge | 70000 |
| Power source type | Battery |

Operational conditions

| | |
|-----------------------------------|-------------|
| Operating relative humidity (H-H) | 5 - 95% |
| Storage temperature (T-T) | -40 - 70 °C |
| Operating temperature (T-T) | -30 - 50 °C |

Ports & interfaces

| | |
|-------------------------|------------------|
| Wireless range | 100 m |
| Connectivity technology | Wired & Wireless |

Weight & dimensions

| | |
|--------|--------|
| Weight | 305 g |
| Height | 185 mm |
| Width | 132 mm |
| Depth | 76 mm |

Scanning

| | |
|---------------------------|-------------|
| Scanner type | 1D/2D |
| Optical sensor resolution | 1280 pixels |
| Wavelength | 660 nm |
| Yaw reading angle | -45 - 45° |
| Pitch reading angle | -65 - 65° |
| Tilt reading angle | -65 - 65° |

Data transmission

| | |
|-------------------|--------|
| Bluetooth version | 4.0 LE |
|-------------------|--------|

Design

| | |
|---------------------|--------------------------------------------------|
| Type | simple |
| RoHS compliance | Yes |
| Protection features | Dust resistant, Shock resistant, Water resistant |