

**Technical details**

Interface	USB + RS-232 + RS-485 + Keyboard Wedge
Cables included	USB
Linear (1D) barcodes supported	Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, Interleaved 2 of 5, MSI, Plessey, U.P.C.
2D (matrix & stacked) barcodes supported	Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
Colour of product	Black
International Protection (IP) code	IP52

**Scanning**

Scanner type	1D/2D
Wavelength	660 nm
Yaw reading angle	-70 - 70°
Pitch reading angle	-70 - 70°
Tilt reading angle	0 - 360°
Motion tolerance (cm/s)	254

**Power**

Input voltage	12
Power source type	USB

**Ports & interfaces**

Connectivity technology	Wired
-------------------------	-------

**Weight & dimensions**

Weight	500 g
Height	143 mm
Width	149 mm
Depth	97 mm

**Operational conditions**

Operating relative humidity (H-H)	5 - 85%
Storage temperature (T-T)	-40 - 70 °C
Operating temperature (T-T)	0 - 40 °C

**Camera**

Sensor type	LED
-------------	-----

**Design**

Type	simple
------	--------