

Miscellaneous

Cables Included	1 x USB cable
Compliant Standards	EN 61000-3-2, EN 61000-3-3, EN55024, EN55022 Class B, RoHS, FIPS 140-2, UL 60950-1, CAN/CSA C22.2 No. 60950-1-07, IP42, EN 50581, IEC 62471, EN 55032 Class B, ICES-003 issue 6 Class B, EN60950-1 (2nd Edition) + A11 + A1 + A12 + A2:2013, EN60950-1 (2nd Edition) + A1 + A2

Processor

Clock Speed	800 MHz
-------------	---------

Dimensions & Weight

Width	2.6 in
Depth	4.2 in
Height	6.6 in
Weight	5.43 oz

Barcode

Interface Type	USB
Minimum Bar Width	3 mil
Scan Element Type	2D imager

Sensor Resolution	1280 x 960
Light Source Wave Length	617 nm
Scan Mode	Single-pass
Skew (Degrees)	60
Pitch (Degrees)	60
Print Contrast Signal (PCS)	16%
Decode Capability	Code 39, QR code, Code 128, Data Matrix
TTL Decoding	Decoded
Connectivity Technology	Wired
OK Notification	Beeper, LED indicator
Features	PRZM Intelligent Imaging technology

Manufacturer Warranty

Service & Support	Limited warranty - 5 years
-------------------	----------------------------

Environmental Parameters

Min Operating Temperature	32 °F
Max Operating Temperature	122 °F
Humidity Range Operating	5 - 95% (non-condensing)

Drop Specification

6 ft to concrete

General

Type

Barcode scanner - handheld

Color

Twilight black

Expansion / Connectivity

Interfaces

1 x USB

Power

Electric Current Required

450 mA (operating)