

JBL IRX108BT Specs

PA Speaker

Configuration	Active 2-Way
Enclosure Type	Bass-Reflex Loudspeaker
Total Power Capacity	1000 W Peak

Drivers

LF Driver	1 x 8" / 203.2 mm
-----------	--------------------------

Performance

Frequency Response	54 Hz to 20 kHz
Maximum SPL	124 dB SPL (Peak)
Coverage Angle	90° H x 60° V (Main)
Speaker Sensitivity	124 dB SPL

I/O Impedance	XLR Mic Input: 10 Kilohms (Balanced)
---------------	--

1/4" TRS Line Input:
10 Kilohms (Balanced)

Protections *None*

Connectivity

Audio I/O **2 x** Combo XLR-1/4" 3-Pin Female
Balanced Line/Mic Input
1 x XLR 3-Pin Male Balanced Line
Thru

Wireless Connectivity Bluetooth

Bluetooth 5.0

Signal Processing

EQ **4 x** Presets (Factory)

Filters *None*

Power

AC Input Power 120 to 240 VAC, 50 / 60 Hz

AC Power Connector **1 x** IEC Input

Power Consumption 200 W

Physical

Mounting **1 x 1.38" / 35 mm Pole Socket (Bottom)**

Handles **2 x Each Side**

Construction Material **Polypropylene**

Dimensions **10.2 x 12.3 x 19.1" / 257.8 x 312.9 x 486.4 mm**

Weight **17.4 lb / 7.9 kg**

Packaging Info

Package Weight **21.6 lb**

Box Dimensions (LxWxH) **20 x 13 x 11"**
