

# Mackie CR3 Specs

## Studio Monitor

---

Monitor Type	Active 2-Way
Enclosure	Bass-Reflex, Unshielded
Power Rating	28 W RMS 50 W Peak
Drivers	LF Driver: <b>1 x</b> 3" / 7.62 cm Polypropylene Cone HF Driver: <b>1 x</b> 0.75" / 19.05 mm Silk Dome
Amplification	<b>1 x</b> Full-Range Amplifier: Class-AB Rated at 28 W RMS / 50 W Peak

---

## Performance

---

Frequency Range	80 Hz to 20 Hz $\pm$ 10 dB
Frequency Response	70 Hz to 20 kHz $\pm$ 3 dB
Maximum Sound Pressure Level (SPL)	97 dB <sup>ⓘ</sup>
Phase Adjustment	<i>None</i>

---

## Signal Processing

---

EQ *None*

---

Filters *None*

---

Parametric EQ *None*

---

## Crossover

---

Crossover Frequency High-Pass Frequency: 3 kHz  
Low-Pass Frequency: 3 kHz

---

## Connectivity

---

I/O **1 x** 1/4" TRS Balanced/Unbalanced Female Analog Input (20 Kilohms)  
**1 x** RCA Unbalanced Female Analog Input (10 Kilohms)  
**1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Input  
**2 x** Push Terminal Unbalanced Female Analog Output  
**1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Output

---

## Power

---

AC Input Power	120 VAC, 60 Hz
----------------	----------------

---

Power Consumption	72 W (Typical)
-------------------	----------------

---

## Environmental

---

Operating Temperature	32 to 104°F / 0 to 40°C
-----------------------	-------------------------

---

## General

---

Enclosure Material	MDF
--------------------	-----

---

Dimensions (W x H x D)	5.5 x 8.2 x 6.2" / 140 x 208 x 158 mm (Each)
------------------------	---

---

Weight	9.0 lb / 4.1 kg (Pair)
--------	------------------------

---

## Packaging Info

---

Package Weight	9.55 lb
----------------	---------

---

Box Dimensions (LxWxH)	16 x 11 x 8"
------------------------	--------------

---