

Studio Monitor

Monitor Type Active 2-Way

Enclosure Bass-Reflex

Power Rating 50 W Peak

Drivers LF Driver: **1 x** 3" / 7.62 cm
Polypropylene Cone
HF Driver: **1 x** 0.75" / 1.91 cm Silk
Dome

Amplification **1 x** Full-Range Amplifier: Class-D50
W Peak

Performance

Frequency Range 70 Hz to 20 kHz (at -10 dB)
80 Hz to 20 kHz (at -3 dB)

Maximum Sound Pressure
Level (SPL) 97 dB

Phase Adjustment *None*

Signal Processing

EQ *None*

Filters *None*

Parametric EQ *None*

Crossover

Crossover Frequency 3 kHz

Connectivity

I/O

- 2 x** 1/4" TRS Balanced/Unbalanced Female Analog Input
- 1 x** 2RCA Unbalanced Female Analog Input
- 1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Input
- 2 x** Push Terminal Unbalanced Female Analog Output
- 1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Output

Power

AC Input Power 100 to 240 VAC, 50/60 Hz

Power Consumption 60 W

Environmental

Operating Temperature 32 to 104°F / 0 to 40°C

General

Enclosure Material MDF

Mounting Points *None*

Dimensions (W x H x D) 5.5 x 8.1 x 7.1" / 14 x 20.6 x 18 cm
(Each)

Weight 7.8 lb / 3.5 kg (Pair)

Packaging Info

Package Weight 9.38 lb

Box Dimensions (LxWxH) 15.6 x 10.3 x 8"
