

Mackie CR4BT Specs

Studio Monitor

Monitor Type	Active 2-Way
Enclosure	Bass-Reflex
Power Rating	50 W Peak
Drivers	LF Driver: 1 x 4" / 10.16 cm Polypropylene Woofer HF Driver: 1 x 0.75" / 1.91 cm Silk Dome Tweeter
Amplification	1 x Full-Range Amplifier: Class-AB Rated at 28 W RMS / 50 W Peak

Performance

Frequency Range	60 Hz to 20 kHz (at -10 dB) 70 Hz to 20 kHz (at -3 dB)
Maximum Sound Pressure Level (SPL)	100 dB
Phase Adjustment	<i>None</i>

Signal Processing

EQ *None*

Filters *None*

Parametric EQ *None*

Crossover

Crossover Frequency 3 kHz

Connectivity

I/O

- 2 x** 1/4" TRS Balanced/Unbalanced Female Analog Input (20 Kilohms)
- 2 x** RCA Unbalanced Female Analog Input (10 Kilohms)
- 1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Input (10 Kilohms)
- 1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Output

Power

AC Input Power 120 VAC, 60 Hz

Power Consumption 72 W

Environmental

Operating Temperature 32 to 104°F / 0 to 40°C

General

Enclosure Material MDF

Mounting Points *None*

Dimensions (W x H x D) 6.1 x 8.8 x 7.3" / 15.5 x 22.4 x 18.5 cm
(Each)

Weight 6.0 lb / 2.7 kg (Each)

Packaging Info

Package Weight 13.2 lb

Box Dimensions (LxWxH) 17.2 x 11.6 x 9.8"
