

Mackie CR4-X Specs

Studio Monitor

Monitor Type	Active 2-Way
Enclosure	Bass-Reflex
Power Rating	50 W Peak
Drivers	LF Driver: 1 x 4" / 10.16 cm Polypropylene Cone HF Driver: 1 x 0.75" / 1.91 cm Silk Dome
Amplification	1 x Full-Range Amplifier: Class-D50 W Peak

Performance

Frequency Range	60 Hz to 20 kHz (at -10 dB) 65 Hz to 20 kHz (at -3 dB)
Maximum Sound Pressure Level (SPL)	100 dB
Phase Adjustment	<i>None</i>

Signal Processing

EQ *None*

Filters *None*

Parametric EQ *None*

Crossover

Crossover Frequency 3 kHz

Connectivity

I/O

- 2 x** 1/4" TRS Balanced/Unbalanced Female Analog Input
- 1 x** 2RCA Unbalanced Female Analog Input
- 1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Input
- 2 x** Push Terminal Unbalanced Female Analog Output
- 1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Output

Power

AC Input Power 100 to 240 VAC, 50/60 Hz

Power Consumption 60 W

Environmental

Operating Temperature 32 to 104°F / 0 to 40°C

General

Enclosure Material MDF

Dimensions (W x H x D) 6.1 x 8.9 x 8.3" / 15.5 x 22.6 x 21.1 cm
(Each)

Weight 10.1 lb / 4.6 kg (Pair)

Packaging Info

Package Weight 11.635 lb

Box Dimensions (LxWxH) 19.9 x 10.9 x 8.9"
