

Mackie EM-89D Specs

Microphone

Form Factor	Handheld / Stand/Boom Mount
-------------	-----------------------------

Sound Field	Mono
-------------	------

Operating Principle	Pressure Gradient
---------------------	-------------------

Capsule	1 x Dynamic
---------	--------------------

Polar Pattern	Cardioid
---------------	----------

Orientation	End Address
-------------	-------------

Circuitry	Solid-State
-----------	-------------

Pad	<i>None</i>
-----	-------------

High-Pass Filter	<i>None</i>
------------------	-------------

Tone Adjustment	<i>None</i>
-----------------	-------------

Indicators	<i>None</i>
------------	-------------

On-Board Controls	<i>None</i>
-------------------	-------------

Windscreen

Built-In

Performance

Frequency Range

50 Hz to 16 kHz

Impedance

600 Ohms \pm 30% at 1 kHz

Sensitivity

-52 dBV/Pa at 1 kHz

Connectivity

Output Connectors
(Analog)

1 x XLR 3-Pin Male (on Mic)

Headphone Connector

None

Number of Conductors

2

Power

Operating Voltage

Not Specified by Manufacturer

Physical

Color

Black

Mounting	Mic Clip (Included)
Dimensions	ø: 2 x L: 7.3" / ø: 5.08 x L: 18.54 cm
Weight	0.66 lb / 0.3 kg

Packaging Info

Package Weight	2.545 lb
Box Dimensions (LxWxH)	13 x 10.5 x 5.7"