

Mackie HM-400 Specs

| | |
|----------------------|--|
| Number of Channels | 4 |
| Input Connections | 2 x XLR 3-pin balanced (one stereo pair) 2 x 1/4" TRS balanced (one stereo pair, also accepts 1/4" TS unbalanced) 1 x 1/4" TRS stereo unbalanced for main input 4 x 1/4" TRS stereo unbalanced for aux inputs |
| Output Connectors | 2 x XLR 3-pin balanced (one stereo pair) 2 x 1/4" TRS balanced (one stereo pair, also accepts 1/4" TS unbalanced) 12 x 1/4" TRS stereo unbalanced headphone outputs |
| Maximum Input Level | Main Input: +15 dBu Aux Input: +20 dBu |
| Maximum Output Level | Headphone Outputs: 550 mW per channel at 47 Ohms (+21 dBu) |
| Input Impedance | Main Input: 20 kOhms balanced, 10 kOhms unbalanced Aux Input: 10 kOhms unbalanced |
| Output Impedance | Headphone Outputs: 3 Ohms unbalanced |

| | |
|------------------------|--|
| Gain Range | Main Input: -66 to +18 dBu |
| Function Controls | Power on/off Main level knob L/R mute switches per channel Stereo/2-Ch switches per channel 2-band EQ per channel Balance knob per channel Output knob per channel |
| Frequency Response | 20 Hz to 20 kHz (± 1 dB) |
| THD | <0.01% (+4 dBu, 1 kHz, unity gain) |
| Noise | -66 dB |
| CMRR | Main Input: >42 dB at 1 kHz |
| Display | 1 x input level meter 4 x output level meters |
| Power Requirement | 100 to 120 VAC, 50/60 Hz, 24 W 220 to 240 VAC, 50/60 Hz, 24 W |
| Power Connector | 1 x 3-pin IEC male, 250 VAC, 10 A |
| Construction Material | Heavy-gauge steel chassis |
| Dimensions (H x W x D) | 1.8 x 19.0 x 8.8" / 46 x 483 x 224 mm |
| Weight | 8 lb / 3.6 kg |

Packaging Info

Package Weight 10.5 lb

Box Dimensions (LxWxH) 20.8 x 10.6 x 4.1"
