

Mackie MDB-1A Specs

Type	Active
Input Connections	1 x 1/4" TS unbalanced
Output Connectors	1 x 1/4" TS unbalanced 1 x XLR 3-pin balanced
Input Impedance	330 kOhms unbalanced
Output Impedance	150 Ohms balanced
Impedance Ratio	2200:1
Pad	-20 dB
High-Pass Filter	120 Hz
Controls	Pad Ground-lift switch Merge Low-cut switch Polarity
Frequency Response	20 Hz to 20 kHz (± 0.5 dB)
Signal to Noise Ratio	90 dB
Dynamic Range	130 dB

Total Harmonic Distortion	0.02% at 1 kHz
---------------------------	----------------

Power Requirement	48 VDC phantom power
-------------------	----------------------

Current	<4 mA DC
---------	----------

Construction Material	Heavy-gauge steel chassis
-----------------------	---------------------------

Dimensions (H x W x D)	1.5 x 3.4 x 5.8" / 38 x 86 x 147 mm
------------------------	-------------------------------------

Weight	0.8 lb / 0.4 kg
--------	-----------------

Packaging Info

Package Weight	1.05 lb
----------------	---------

Box Dimensions (LxWxH)	6.9 x 5.8 x 2.9"
------------------------	------------------
