



MX SERIES AMPLIFIERS SPECIFICATIONS

Continuous Sine Wave Average Output Power, per channel, both channels driven, 20 Hz to 20 kHz

	-	.,	^	_	_	_	
n	Л	x	"	h	0		٠
Ш	Λ.	Л	_	v	u	u	

8 Ω Bridged Power:	1500 W
8 Ω Dual Power:	500 W
4 Ω Dual Power:	750 W

MX3500:

8 Ω Bridged Power:	2700 W
8 Ω Dual Power:	1000 W
4 Ω Dual Power:	1350 W

Frequency Response

Distortion (THD)

20 Hz – 20 kHz:	<0.5%
-----------------	-------

Signal-to-Noise Ratio (20 Hz - 20 kHz)

MX2500:	>104 dB below rated power, A-weighted
MX3500:	>105 dB below rated power, A-weighted

Damping Factor

>200 @ 10 Hz to 400 Hz into 8 Ω
7200 @ 10 HZ 10 400 HZ 11110 6 52

Slew Rate

Input Gain	
MX2500:	33 dB
MX2300·	37 dB

Input / Output

input / Output	
Input Type:	Female XLR Balanced
XLR Impedance:	20 k Ω balanced
	10 kΩ unbalanced
Output Type:	Speakon®
	Male XLR Balanced [Thru]
Speakon Out Impedance:	600 Ω balanced
XLR Thru Out Impedance:	600 Ω balanced

Line Input Power

MX3500: AC Connector:	~230-240VAC, 50-60 Hz, 1000W @ 8 Ω 3-pin IEC 250 VAC, 10 A male
Detachable line cord: MX2500:	~230–240VAC, 50–60 Hz, 500W @ 8 Ω

Safety Features

Input Protection:	Peak and RMS limiting, power
	supply and amplifier thermal protection
Cooling:	Variable-speed fans with back-to-front airflow
Channel Display LEDs:	Power, Signal, Clipping, Fault

Physical Properties (product)

MX2500:

Height:	3.5 in / 88 mm
Width:	19.0 in / 483 mm
Depth:	11.9 in / 303 mm
Weight:	30.4 lb / 13.8 kg

MX3500:

Height:	3.5 in / 88 mm
Width:	19.0 in / 483 mm
Depth:	14.6 in / 370 mm
Weight:	40.3 lb / 18.3 kg

Physical Properties (packaged product)

MX2500:

>10V/us

Height:	6.1 in / 155 mm
Width:	22.9 in / 582 mm
Depth:	21.1 in / 536 mm
Weight:	35.5 lb / 16.1 kg

MX3500:

Height:	6.1 in / 155 mm
Width:	22.9 in / 582 mm
Depth:	21.1 in / 536 mm
Weight:	45.4 lb / 20.6 kg



MX SERIES AMPLIFIERS SPECIFICATIONS CONTINUED...

Ordering Information

MX2500 2500W Professional Power Amplifier, US	P/N 2050850-00
MX2500 2500W Professional Power Amplifier, EU	P/N 2050850-01
MX2500 2500W Professional Power Amplifier, CN	P/N 2050850-05
MX3500 3500W Professional Power Amplifier, US	P/N 2050860-00
MX3500 3500W Professional Power Amplifier, EU	P/N 2050860-01
MX3500 3500W Professional Power Amplifier, CN	P/N 2050860-05

MX SERIES AMPLIFIERS DIMENSIONS

