

Mackie Onyx Producer Specs

Interface

Channels of I/O **Analog:**
2 Inputs / 2 Outputs at 192 kHz

Max Sample Rate/Resolution 192 kHz / 24-Bit

Display and Indicators **2 x** LEDs (Clip, Signal)
1 x LED (Host Connection)
1 x LED (MIDI)

Connectivity

Host Connection **1 x** USB Type-B (USB 2.0)

Analog I/O **2 x** Combo XLR-1/4" TRS Balanced Mic Input
1 x 1/4" TRS Unbalanced Headphone Output
2 x 1/4" TRS Balanced Monitor Output

Phantom Power +48 V

Digital I/O *None*

MIDI I/O **1 x** 5-Pin MIDI In

1 x 5-Pin MIDI Out

Memory Card Slot

None

Performance

Frequency Response

Inputs, Outputs:

20 Hz to 20 kHz ± 0.5 dB (Min Gain)

Max Input Level

Mic Inputs:

+11 dBu (Min Gain)

Line/Hi-Z Inputs:

+24 dBu (Min Gain)

Max Output Level

Monitor Outputs:

+10 dBu

Headphone Outputs:

+10 dBu

THD

Mic Inputs:

Line/Hi-Z Inputs:

Monitor Outputs:

Headphone Outputs:

EIN

Mic/Line/Hi-Z Inputs:

< -100 dB

Monitor Outputs:

< -85 dBu

Headphone Outputs:

< -75 dBu

Digital Audio

Sample Rates	Up to 192 kHz
--------------	---------------

Bit Depth	Up to 24-Bit
-----------	--------------

Sync Sources	Internal
--------------	----------

Compatibility

OS Compatibility	macOS Windows
------------------	------------------

Required Hardware	Available USB 2.0 Port
-------------------	------------------------

Power

Power Requirements	USB Bus-Power
--------------------	---------------

Physical

Anti-Theft Features	Kensington Security Slot
---------------------	--------------------------

Dimensions	7.4 x 4.49 x 2.01" / 18.8 x 11.4 x 5.1 cm
------------	---

Weight	1.4 lb / 0.6 kg
--------	-----------------

Packaging Info

Package Weight	2.065 lb
----------------	----------

Box Dimensions (LxWxH)	11.6 x 6.5 x 3.15"
------------------------	--------------------
