

Mackie SRM1850 Specs

PA Speaker

Configuration	Active Subwoofer
---------------	------------------

Enclosure Type	Bass-Reflex Subwoofer
----------------	-----------------------

Total Power Capacity	800 W RMS 1600 W Peak
----------------------	--------------------------

Amplifier Class	Class-D
-----------------	---------

Drivers

LF Driver	1 x 18" / 457 mm Paper Woofer
-----------	--------------------------------------

LF Voice Coil	3" / 76 mm
---------------	------------

Magnet	Ferrite
--------	---------

Performance

Frequency Response	40 Hz to 120 Hz -3 dB 35 Hz to 150 Hz -10 dB
--------------------	---

Maximum SPL 132 dB

I/O Impedance **Input:**
20 Kilohms (Balanced)
10 Kilohms (Unbalanced)

THD

Protections RMS, Thermal

Connectivity

Audio I/O **2 x** XLR Female Balanced Input
2 x XLR Male Balanced Line Output
2 x XLR Male Balanced High-Pass Output ⓘ

Signal Processing

Crossover 60 to 120 Hz ⓘ

Dynamic Processing Peak Limiter

Alignment Delay Yes

Power

AC Input Power 100 to 120 VAC, 60 Hz

AC Power Connector	1 x IEC
--------------------	----------------

Power Consumption	200 W
-------------------	-------

Physical

Handles	2 x Side
---------	-----------------

Cooling	Convection
---------	------------

Construction Material	Metal Grille, Plywood
-----------------------	-----------------------

Operating Temperature	32 to 104°F / 0 to 40°C
-----------------------	-------------------------

Dimensions	22.5 x 22.2 x 23.9" / 572 x 565 x 608 mm
------------	--

Weight	64 lb / 29 kg
--------	---------------

Packaging Info

Package Weight	83 lb
----------------	-------

Box Dimensions (LxWxH)	29 x 27.5 x 25"
------------------------	-----------------
