

# Mackie SRM-FLEX Specs

## Portable PA System

---

Speaker Configuration      **1 x** 2-Way Speaker Column with Subwoofer

---

Number of Input Channels      6 (2 x Mono, 2 x Stereo)

---

Amplifier Power Rating      **Total:**  
1300 W Peak  
**LF:**  
1000 W Peak  
**HF:**  
300 W Peak

---

Amplifier Class      **HF/LF:**  
Class-D

---

## Speakers

---

Enclosure Type      **Speaker:**  
Sealed  
**Subwoofer:**  
Sealed

---

HF Driver      **6 x** 2" / 5.08 cm Dome Tweeter

---

LF Driver      **1 x** 10" / 25.4 cm Woofer

---

Magnet

**LF Driver:**  
Ferrite

---

## Signal Processing

---

Crossover

600 Hz, 18 dB/Octave Butterworth  
(Internal)

---

EQ

**1 x LF Shelf:**  
-15 to +5 dB at 90 Hz (per Channel)  
**1 x HF Shelf:**  
-15 to +5 dB at 6 kHz (per Channel)

---

Semi-Parametric EQ

*None*

---

Effects

**3 x** Reverb

---

Filters

*None*

---

Dynamic Processing

*None*

---

## Performance

---

Frequency Range

**System:**  
40 Hz to 20 kHz -10 dB  
**System:**  
50 Hz to 20 kHz 3 dB

---

Maximum SPL

118 dB (Peak)

---

|                |  |
|----------------|--|
| Coverage Angle | 90° H x 40° V  |
| Gain Range     | <b>Mic/Line Input:</b><br>Up to +16 dB<br><b>Bluetooth:</b><br>Up to +10 dB  |
| I/O Impedance  | <b>XLR Mic Input:</b><br>8 Kilohms (Balanced)<br><b>XLR Line Input:</b><br>8 Kilohms (Balanced)<br><b>1/4" TRS Line Input:</b><br>8 Kilohms (Balanced)<br><b>1/4" TS Hi-Z Input:</b><br>1 Megohms (Unbalanced)<br><b>XLR Line Output:</b><br>600 Ohms (Balanced) |
| Protections    | Infrasonic, Output Limiter, Power Supply, RMS, Thermal   |

## Connectivity

|             |  |
|-------------|--|
| Audio I/O   | <b>2 x</b> Combo XLR-1/4" TRS Female<br>Balanced/Unbalanced Mic/Line/Hi-Z<br>Input<br><b>2 x</b> 1/4" TRS Female<br>Balanced/Unbalanced Line Input<br><b>1 x</b> 1/8" / 3.5 mm TRS Female<br>Unbalanced Aux Input<br><b>1 x</b> XLR 3-Pin Male Balanced Line<br>Output |
| USB         | <i>None</i>  |
| Network I/O | <i>None</i>  |

---

|                       |           |
|-----------------------|-----------|
| Wireless Connectivity | Bluetooth |
|-----------------------|-----------|

---

## Bluetooth

---

|           |     |
|-----------|-----|
| Bluetooth | 4.2 |
|-----------|-----|

---

|         |        |
|---------|--------|
| Pairing | Manual |
|---------|--------|

---

|                       |   |
|-----------------------|---|
| Bluetooth Power Class | 1 |
|-----------------------|---|

---

## Power

---

|                |                            |
|----------------|----------------------------|
| AC Input Power | 100 to 240 VAC, 50 / 60 Hz |
|----------------|----------------------------|

---

|                   |       |
|-------------------|-------|
| Power Consumption | 110 W |
|-------------------|-------|

---

|                    |                      |
|--------------------|----------------------|
| AC Power Connector | <b>1 x</b> IEC Input |
|--------------------|----------------------|

---

## Physical

---

|                   |   |
|-------------------|---|
| Transport Options | <b>1 x</b> Carry Case<br><b>Subwoofer:</b><br><b>1 x</b> Handle (Top) |
|-------------------|---|

---

|         |            |
|---------|------------|
| Cooling | Convection |
|---------|------------|

---

|                       |  |
|-----------------------|--|
| Construction Material | Perforated Metal Grille,<br>Polypropylene, Steel |
|-----------------------|--|

---

|                       |                         |
|-----------------------|-------------------------|
| Operating Temperature | 32 to 104°F / 0 to 40°C |
|-----------------------|-------------------------|

---

|            |   |
|------------|---|
| Dimensions | 79 x 14.2 x 13" / 200.66 x 36.07 x 33.02 cm (Full Assembly) |
|------------|---|

---

|        |                    |
|--------|--------------------|
| Weight | 29.6 lb / 13.43 kg |
|--------|--------------------|

---

## Packaging Info

---

|                |       |
|----------------|-------|
| Package Weight | 42 lb |
|----------------|-------|

---

|                        |               |
|------------------------|---------------|
| Box Dimensions (LxWxH) | 27 x 23 x 20" |
|------------------------|---------------|

---