

# Mackie Thump Specs

## PA Speaker

---

Configuration	Active 2-Way
---------------	--------------

---

Total Power Capacity	1300 W
----------------------	--------

---

Amplifier Power Rating	<b>LF:</b> 1000 W <b>HF:</b> 300 W
------------------------	---

---

## Drivers

---

HF Driver	<b>1 x</b> 1.4" / 35.6 mm Titanium Dome Compression Driver
-----------	--

---

LF Driver	<b>1 x</b> 15" / 38.1 cm Woofer
-----------	---------------------------------

---

## Performance

---

Frequency Response	32 Hz to 23 kHz
--------------------	-----------------

---

Maximum SPL	127 dB
-------------	--------

---

Coverage Angle	90° H x 60° V
----------------	---------------

---

Protections

RMS, Thermal

---

## Connectivity

---

Audio I/O

**2 x** Combo XLR-1/4" Input  
**1 x** XLR Output

---

## Signal Processing

---

Dynamic Processing

Peak Limiter

---

Alignment Delay

Yes

---

## Power

---

AC Input Power

**Universal:**  
100 to 240 VAC, 50 / 60 Hz

---

AC Power Connector

**1 x** IEC

---

## Physical

---

Mounting

Pole Socket

---

Construction Material

Metal Grille, Polypropylene

---

Dimensions 14 x 17.4 x 27" / 35.6 x 44.2 x 68.6 cm

---

Weight 40 lb / 18.1 kg

---

## Packaging Info

---

Package Weight 42 lb

---

Box Dimensions (LxWxH) 30 x 19 x 16.5"

---