

GENERAL

General type	B/W desktop printer for A4 format
Technology	KYOCERA ECOSYS Laser
Engine speed	Up to 35 pages per minute in A4
Resolution	300 dpi, 600 dpi, 1200 dpi
Warm-up time	Approx. 15 seconds or less from power on
Time to first print	Approx. 6.8 seconds or less
Dimensions (W x D x H)	Main unit: 375 x 393 x 272 mm
Weight	Main unit: Approx. 14 kg
Power consumption	Printing: 620 W, Ready mode: 8 W, Sleep mode:: 0.8 W
Power source	AC 220 ~ 240 V, 50/60 Hz
Noise (ISO 7779)	Noise (ISO 7779 / ISO 9296) Printing: 47.9 dB(A) LpA, Ready/Standby mode: Immeasurably low Sleep mode: Immeasurably low
Safety standards	TÜV/GS, CE - This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.
General memory	Standard 256 MB, max. 256 MB

PAPER HANDLING

Input capacity	100-sheet multi-purpose tray; 60 – 220 g/m ² ; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm – 216 x 356 mm) 250-sheet universal cassette; 60 – 163 g/m ² ; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 – 216 x 356 mm).
Max. input capacity with options	850 sheets A4
Duplex unit	Duplex functionality as standard: Double-sided printing: 60 – 163 g/m ² ; A4, A5, B5, Letter, Legal

Max. output capacity	250 sheets face-down
----------------------	----------------------

General paper handling	All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
------------------------	--

PRINT

Processor	800MHz
-----------	--------

Controller language	PRESCRIBE IIe
---------------------	---------------

Emulations	PCL 6 (PCL 5e/PCL-XL), PostScript 3 (KPD L 3), PDF Direct Print, XPS/OpenXPS
------------	--

Fonts	93 scalable fonts for PCL6/KPDL3, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)
-------	--

Applicable OS	All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request
---------------	---

INTERFACES

Standard interface	USB 2.0 (Hi-Speed), USB Host Interface (dedicated for card reader or service purposes), Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Slot for optional SD/SDHC-Card
--------------------	--

WARRANTY

Warranty	1-year warranty as standard (depending on the country). KYOCERA guarantees the drum and developer for 3 years or maximum 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.
----------	--
