Diagonal Viewing Size: 49.53 cm (19.5 inches) Horizontal: 432.96 ± 0.96 mm (17.05 inches) 238.05 ± 1.71 mm (9.37 inches) **Maximum Preset Resolution:** 1600 x 900 at 60 Hz Aspect Ratio: **Pixel Pitch:** 0.27 mm x 0.27 mm Pixel Per Inch (PPI): Brightness: 250 cd/m² (typical) **Color Support:** Color gamut (typical): 83% (CIE1976) 72% (CIE1931) Color depth: 16.7 Million Contrast Ratio: 1000:1 (typical) Viewing Angle: 160°/170° Response Time: 5 ms typical (Normal) (gray to gray) Panel Type: TN (Twisted Nematic) **Display Screen Coating:** Backlight Technology: ComfortView with Flicker-free screen: **Dell Display Manager Compatibility:** Yes Remote Asset Management : Yes, via Dell Command I Monitor GSA/TAA: **Optional Soundbar:** AC511 - usb powered via PC AE515 Skype for Business Certified Connectivity Connectors 1 X VGA 1 X DisplayPort 1.2 **HDCP Support** DisplayPort HDCP 1.2 Security Adjustability

Dimensions & Weight Dimensions (with stand)

Flat Panel Mount Interface VESA (100 mm)

Tilt Only (-5° to 21°)

Security lock slot (cable lock sold separately)

Security

Height

368.96 mm (14.53 inches) **Width**

471.52 mm (18.56 inches)

Depth

171.0 mm (6.73 inches)

Weight

Weight (panel only - for VESA mount/ no cables)
2.20 kg (4.85 lb)
Weight (monitor + cables)
2.94 kg (6.48 lb) Weight (with packaging) 3.94 kg (8.68 lb)

Power

AC input voltage/frequency/current

100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 0.7 A (typical)

Power Consumption (Operational) 11W (Typ). 14W (Max). 10.7W (Energy Star)

Power Consumption Stand by/Sleep

Less than 0.3W

Warranty

Standard Service Plan

3 Years Advanced Exchange Service and Limited Hardware Warranty

Optional Service Plan

Dell ProSupport

Environmental Compliance

ENERGY STAR®, EPEAT® registered where applicable, TCO Certified Display

What's in the Box

Components

Monitor with stand

Cables

Power cable

1 X DP Cable (DP to DP)
1 X VGA Cable (EMEA and Japan only)
1 X VESA screw cover

Documentation

Quick Setup Guide

Safety and regulatory information