

Compatibility Information

Designed For	Lenovo ThinkBook 14s-IML 20RS Lenovo ThinkCentre M715q (2nd Gen) 10VK Lenovo ThinkCentre M75q-1 11A4, 11A5 Lenovo ThinkCentre M75s-1 11AA, 11AV Lenovo ThinkCentre M90n-1 IoT 11AJ Lenovo ThinkPad E14 20RB Lenovo ThinkPad E15 20RE Lenovo ThinkPad L13 Yoga 20R5, 20R6 Lenovo ThinkPad T490 20RX, 20RY Lenovo ThinkPad X1 Carbon (7th Gen) 20R2 Lenovo ThinkPad X1 Yoga (4th Gen) 20SB Lenovo ThinkPad X390 20SC, 20SD
--------------	--

Miscellaneous

Cables Included	1 x DisplayPort cable - 6 ft 1 x VGA cable - 6 ft 1 x SuperSpeed USB cable - 6 ft
Compliant Standards	FCC Class B certified, RoHS, ISO 9241-307, WEEE, DDC-2B/CI
Localization	English
Security Slot Type	Kensington security slot

Manufacturer Warranty

Service & Support	Limited warranty - 3 years Limited warranty - backlight - 3 years
-------------------	---

Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
------------------------------	--

Tilt Angle	-5/+30
Swivel Angle	90
Rotation Angle	90
Height Adjustment	4.3 in
VESA Mounting Interface	100 x 100 mm
Flat Panel Mount Interface	100 x 100 mm

Environmental Parameters

Min Operating Temperature	32 °F
Max Operating Temperature	104 °F
Humidity Range Operating	10 - 80%

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	23"
Viewable Size	23"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9

Native Resolution	Full HD (1080p) 1920 x 1080
Pixel Pitch	0.2652 mm
Pixel Per Inch	95.8
Brightness	250 cd/m ²
Contrast Ratio	1000:1
Response Time	6 ms
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	178
Backlight Technology	WLED
Features	Wide Viewing Angle
Color	Black
Dimensions (WxDxH)	20.6 in x 10.4 in x 13.3 in - with stand
Weight	10.85 lbs

Connectivity

Interfaces	VGA HDMI (HDCP) DisplayPort (HDCP) 4 x USB 3.0 downstream USB 3.0 upstream
------------	--

Environmental Standards

TCO Certified	TCO Certified Displays 7, TCO Certified Edge
---------------	--

Displays

ENERGY STAR Certified Yes

Power

Voltage Required AC 120/230 V (50/60 Hz)

Power Consumption Operational 16 Watt

Power Consumption Stand by 0.5 Watt

Power Consumption Sleep 0.5 Watt