

General	
Panel Type	0.64" LCD x 3
Lamp	280W x 1
Brightness	5000 lumens
Lens	F1.60-2.12, f15.30-24.64mm
Contrast (Full on / Full off)	16000:1
Resolution (Native / maximum)	WUXGA
Video Compatibility	PAL, PAL-M, PAL-N, PAL60, "PAL, PAL-M, PAL-N, PAL60, SECAM, NTSC, NTSC4.43
Screen Size	30" - 300"
Lens Shift	Vertical +44°
Keystone Correction Range	Vertical ±25°; horizontal ±30°
Weight	Approx 4.9kg
Dimensions (W x H x D)	389 x 125 x 332 mm
Power Consumption	410W (Standby mode : 0.5W(eco), 14W(normal))
Terminals	HDMI (19-pin x 2) PC1 (D-sub 15-pin x 1) PC2 in/mon out (D-sub 15-pin x 1) Video (Pin jack x 1) Audio 1(M3 stereo mini jack (L/R x 1) Audio 2(M3 stereo mini jack x1/mic in) Audio 3(Pin jack (L/R) x 1) Audio out (M3 stereo mini jack (L/R) x 1(mon out)) Serial (D-sub 9-pin x 1) USB A (Type A Memory Viewer/Pairing function x 1) USB B (Type B for USB display x 1) LAN/Digital Link (RJ-45 x 1 for network connection, DIGITAL LINK, 100Base-TX, compatible with PLink, HDCP Compatible, Deep Color compatible)
Replacement Lamp	ET-LAV400
Optional Accessories	ET-RFV410 (Replacement filter unit)
Optional Lens	--

Standard Accessories	CD-ROM software Lens cap RGB cable Power cord Battery for remote control unit Wireless remote control unit
-------------------------	---