


CAT.6 Unshielded 48 Port Patch Panel

Avalon CAT.6 48 Port Patch Panels are the industry's high-quality panels that support the latest technologies and diverse applications. These panels combine strength and durability with a sleek look, making them ideal for all kinds of environments. These comply with ANSI/TIA-56-2, ISO/IEC 11801 and EN 50173-1 Class E specifications. The complete module complies with EU ROHS directive. The construction is in standard 19" size and suits all 19" rack installations.

Features

- High density 48 port 2U patch panel
- UTP Snap-in Type
- Six Port RJ45 modules applied
- Suitable for Cat.6 UTP Keystone Jacks
- Integral plastic cable management
- Modern design and simplicity of mounting



Specifications

- Thickness of cold-rolled steel: 1.5mm
- Operating Temperature Range : -60°C to 80°C
- IDC Accept: 22-26 AWG
- Wire Scheme: T568A/B
- Insulation Resistance: 500Ω
- Current Rating: 1.5Amps
- DC Resistance: 0.1 ohm MAX
- Voltage: 150 VAC MAX
- Plug Retention Force: 89N
- Spring Wire: Phosphor Bronze With Gold-plated 3u-50u
- IDC Contact: Phosphor Bronze
- Specifically Design: With Two PCB Panel & Tool-less
- Insertion life: ≥1000 mating cycles
- Plug /Jack Contact Force: 100g min
- Humidity: 5 to 93% (non-condensing)

Applications

- 1000 Base-TX Gigabit Ethernet
- 1000 Base-T Gigabit Ethernet
- 100 Base-TX Fast Ethernet
- 10 Base-T Ethernet
- Voice, Video and other applications
- Standard Size for mounting in 19" Racks and Cabinets

Ordering Information

Part No	Description
ANC6UPP-48	CAT.6 Unshielded 48 Port Patch Panel