

<b>Model Description</b>	ProSAFE® 48-Port Gigabit Smart Switch
<b>Datasheet (PDF)</b>	<a href="#">GS748Tv5 Datasheet</a>
<b>10/100Mbps ports</b>	N/A
<b>Gigabit ports</b>	48
<b>SFP ports</b>	4 SFP: 2 combo, 2 dedicated
<b>Number of PoE ports</b>	N/A
<b>PoE+ (802.3at)</b>	N/A
<b>Total PoE Power budget (Watts)</b>	N/A
<b>Max MAC entries</b>	16K
<b>Buffer size</b>	2MB
<b>VLAN (Number Supported)</b>	256

<b>VLAN routing</b>	Yes
<b>Dynamic VLAN assignment</b>	Yes
<b>MLD Snooping</b>	Yes
<b>Static route</b>	Yes
<b>Host ARP table</b>	512
<b>EEE</b>	Yes
<b>DoS Prevention</b>	Yes
<b>Internal/External</b>	Internal 100-240VAC 50-60Hz
<b>Max consumption (Watts)</b>	41,1
<b>FAN</b>	2
<b>Acoustic Noise Level @25C (dBA)</b>	37.2 dBA
<b>Operating</b>	0° to 50° C

**Temperature**

**MTBF**

390,728 hours

**Weight (kg)**

3,46

**Dimensions  
(WxDxH) mm**

440x257x43