

# Warm Audio WA-47JR Specs

## Microphone

---

Sound Field	Mono
-------------	------

---

Operating Principle	Pressure Gradient
---------------------	-------------------

---

Capsule	Condenser
---------	-----------

---

Polar Pattern	Cardioid, Figure-8, Omnidirectional
---------------	-------------------------------------

---

Pattern Selection	Switched
-------------------	----------

---

Circuitry	Tube
-----------	------

---

Pad	-10 dB
-----	--------

---

High-Pass Filter	70 Hz
------------------	-------

---

## Performance

---

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

---

Maximum SPL	147 dB SPL ⓘ
-------------	--------------

---

Impedance	100 Ohms
-----------	----------

---

Load Impedance	1 Kiloohms
Sensitivity	10 mV/Pa
Dynamic Range	138 dB A-Weighted
Signal-to-Noise Ratio	85 dB A-Weighted
Equivalent Noise Level	9 dB A-Weighted

## Connectivity

---

Output Connectors (Analog)	<b>1 x</b> XLR 3-Pin
----------------------------	----------------------

## Power

---

Operating Voltage	48 V
-------------------	------

## Physical

---

Dimensions	ø: 2.05 x L: 8.27" / ø: 52 x L: 210 mm
Weight	1.1 lb / 0.5 kg

## Packaging Info

---

Package Weight

3.83 lb

---

Box Dimensions (LxWxH)

11.15 x 10 x 6.2"

---