

Warm Audio WA-84 Specs

Microphone

Form Factor	Stand/Boom Mount
-------------	------------------

Sound Field	Mono
-------------	------

Operating Principle	Pressure Gradient
---------------------	-------------------

Capsule	Condenser
---------	-----------

Polar Pattern	Cardioid
---------------	----------

Orientation	End Address
-------------	-------------

Circuitry	Solid-State
-----------	-------------

Pad	-10 dB
-----	--------

High-Pass Filter	<i>None</i>
------------------	-------------

Tone Adjustment	<i>None</i>
-----------------	-------------

On-Board Controls	Pad
-------------------	-----

Windscreen	Foam (Included)
------------	-----------------

Performance

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	133 dB SPL
-------------	------------

Impedance	200 Ohms
-----------	----------

Load Impedance	1 Kilohms
----------------	-----------

Sensitivity	-39 dB at 1 kHz
-------------	-----------------

Dynamic Range	107 dB A-Weighted
---------------	-------------------

Signal-to-Noise Ratio	78 dB A-Weighted
-----------------------	------------------

Equivalent Noise Level	16 dB A-Weighted
------------------------	------------------

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin Male (Locking, on Mic)
----------------------------	---

Power

Operating Voltage	48 V (Phantom Power)
-------------------	----------------------

Physical

Color	Nickel
-------	--------

Mounting	Mic Clip, Shockmount (Included)
----------	---------------------------------

Construction Material	Metal
-----------------------	-------

Dimensions	ø: 0.87 x L: 5.2" / ø: 22 x L: 132 mm
------------	---------------------------------------

Weight	4.3 oz / 122 g
--------	----------------

Packaging Info

Package Weight	2.57 lb
----------------	---------

Box Dimensions (LxWxH)	12 x 7.4 x 4"
------------------------	---------------
