

Specification

Show all Hide all ▾

Display/image

Display technology	DLP
Resolution	UHD (3840x2160)
Brightness	3,500 lumens
Contrast ratio	2,500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	90%
Screen size	2.16m ~ 3.05m (85" ~ 120") diagonal

▾ Lamp info

Light source type	Laser
LASER life	20,000 hours

▾ Optical

Throw ratio	0.25:1
Projection distance (m)	0.47m - 0.66m
Focal length (mm)	525
Lens shift	Vertical +0%
Native offset	124%

▾ Connectivity

Connections	Inputs 3 x HDMI 2.0, 1 x USB-A reader Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x USB-A service, 1 x RJ45
-------------	--

▾ General

Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
3D compatibility	Frame-pack: 1080p24, 720p50 / 60
3D	Full 3D
Security	Kensington Lock, Password protected interface
OSD / display languages	11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Yes
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Rechargeable remote control Basic user manual
Input lag	70.00ms

▼ Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	220W
Power consumption (max)	345W

▼ Weight and dimensions

Net weight	11kg
Dimensions (W x D x H) mm	576 x 383 x 130
