

HARDWARE FEATURES

Interface	<ul style="list-style-type: none">• 2× 10/100 Mbps Ethernet Port• 1× USB 2.0 Port• 1× Micro USB Port
Power Supply	802.3af/at PoE or Micro USB (DC 5V/Minimum 1A)
Dimensions	3.9×3.9×1.0 in (100×98×25 mm)

MANAGEMENT

Omada App	Yes
Centralized Management	Up to 100 Omada access points, JetStream switches, and SafeStream routers
Cloud Access	Yes
L3 Management	Yes
Multi-site Management	Yes
Management Features	<ul style="list-style-type: none">• Automatic Device Discovery• Batch Configuration• Batch Firmware Upgrading• Intelligent Network Monitoring• Abnormal Event Warnings• Unified Configuration• Reboot Schedule• Captive Portal Configuration

OTHERS

Certification	CE, FCC, RoHS
Package Contents	<ul style="list-style-type: none">• Omada Hardware Controller OC200• Quick Installation Guide• Ethernet Cable
System Requirements	Microsoft® Windows®10, 8, 7, Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux
Environment	<ul style="list-style-type: none">• Operating Temperature: 0–40 °C (32–104 °F)• Storage Temperature: -40–70 °C (-40–158 °F)• Operating Humidity: 10–90% RH non-condensing• Storage Humidity: 5–90% RH non-condensing