

Display

| | | | |
|---------------------------------|--------------------------------|---------------------------|----------------|
| Native Resolution | WUXGA 1920x1200 | Maximum Resolution | 4K 4096 x 2160 |
| Contrast Ratio (typical) | 10,000:1 with dynamic contrast | | |

Synchronization Range

| | | | |
|------------------------------------|---------------------------------------|-----------------|-------------------------------------|
| Horizontal (Analog/Digital) | Analog: 15-100kHz, Digital: 15-153kHz | Vertical | Analog: 48-120Hz, Digital: 24-120Hz |
|------------------------------------|---------------------------------------|-----------------|-------------------------------------|

Signal Compatibility/Connectivity

| | | | |
|----------------------------------|--|---|--|
| Supported Video Standards | NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM | SD/HD Video Signal Compatibility | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| PC Signal Compatibility | VGA, SVGA, XGA, SXGA, SXGA+, WXGA, UXGA, FHD, WUXGA, 2K, QXGA, WQXGA, 4k | Macintosh Signal Compatibility | Yes |
| Sync Compatibility | Separate Sync / Composite Sync / Sync on G | External Control | RS-232, IR, HDBaseT, Stereo Mini, PJ-45 |

Input Terminals

RGB1(analog):
VGA 15-pin D-sub
RGB2(analog):
5-BNC
RGB2(digital):
HDMI w/HDCP
RGB4(digital):
DisplayPort w/HDCP
RGB5(digital):
HDBaseT

Output Terminals

Monitor Out:
HDMI

Power Consumption (typical)

| | | | |
|---------------------------|----------------------------|----------------------|-----------|
| On | 1220W / 625W / 4.3W / 0.2W | Input Current | 11.6-5.2A |
| Power Requirements | 100-240V AC, 50/60 Hz | | |

Physical Specifications

Dimensions (WxHxD)

Product:
19.7 x 22.9 x 8.5 in. / 500 x 583 x 216mm

Weight

Net Weight:
63.9 lbs. / 29.0 kg

Environmental Conditions

Operating Temperature 41-104°F / 5-40°C

Storage -14-122°F / -10-50°C

Limited Warranty (parts & labor)

5 year or 20,000 hour parts & labor warranty. First year InstaCare Service.