

Jabra Speak 750 Specs

Speaker

Frequency Response	150 Hz to 20 kHz
--------------------	------------------

Power Output	10 W
--------------	------

Signal to Noise Ratio	70 dB
-----------------------	-------

Microphone

Pickup Pattern	Omnidirectional
----------------	-----------------

Microphone Coverage	360°
---------------------	------

Beamforming Support	No
---------------------	----

Technology

Duplex Mode	Echo Cancellation, Full-Duplex (FDX)
-------------	--------------------------------------

Active Noise Cancellation	Yes
---------------------------	-----

Connectivity

USB Connections	1 x USB Type-A USB 2.0 (Male)
-----------------	--------------------------------------

Ethernet Ports	<i>None</i>
Audio Ports	<i>None</i>
Telephone Ports	<i>None</i>
Wireless Technology	Bluetooth 4.2
Supported Bluetooth Profiles	HSP 1.2 HFP 1.6 A2DP 1.2 AVRCP 1.5
NFC	No
Supported Communications	Avaya, Cisco, Unified Communication
WLAN Mode	<i>None</i>
Wireless Range	98.4' / 30 m

Environmental

Operating Temperature	32 to 113°F / 0 to 45°C
Storage Temperature	-40 to 113°F / -40 to 45°C

Power

Battery Capacity	500 mAh
Battery Voltage	5 V

Talk Time	11 Hours
-----------	----------

Recharge Time	3 Hours
---------------	---------

Physical

LED Indicators	Yes
----------------	-----

Lock Slot	Yes, Kensington
-----------	-----------------

Dimensions	1.5 x 5.2" / 38.0 x 131.0 mm
------------	------------------------------

Weight	10.62 oz / 301 g
--------	------------------

Packaging Info

Package Weight	1.02 lb
----------------	---------

Box Dimensions (LxWxH)	6.2 x 6 x 2.2"
------------------------	----------------
