

PANEL

Screen Size	49"
Panel Technology	IPS
Aspect Ratio	16:9
Native Resolution	1,920 x 1,080 (FHD)
Brightness(Typ.,cd/m ²)	450
Contrast Ratio	1,300:1
Dynamic CR	500,000 : 1 (The luminosity ratio of Full Black/Full White color on video input condition.)
Viewing Angle (H x V)	178 x 178
Response Time	8 ms (G to G)
Surface Treatment (Haze)	3%
Life Time (Typ.)	60,000 Hrs
Operation Hours	24 Hrs
Orientation	Landscape & Portrait

CONNECTIVITY

Input	HDMI, DP, DVI-D, RGB, Audio, USB 2.0
Output	DP, Audio
External Control	RS232C In/out, RJ45 (LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Width	2.25 mm (T/L), 1.25 mm (B/R)
Monitor Dimension (W × H × D)	1,077.6 x 607.8 x 89.7 mm
Weight (Head)	17.8 kg
Carton Dimensions (W × H × D)	1,214 x 778 x 263 mm
Packed Weight	22.8 kg
VESA™ Standard Mount Interface	600 x 400 mm

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
-----------------------	-------------

Operation Humidity	10 % to 80 %
--------------------	--------------

POWER

Power Supply	100-240V~, 50/60Hz
--------------	--------------------

Power Type	Built-In Power
------------	----------------

POWER CONSUMPTION

Typ.	90 W
------	------

Max.	110 W
------	-------

Smart Energy Saving	55 W
---------------------	------

CERTIFICATION

Safety	CB / NRTL
--------	-----------

EMC	FCC Class "A" / CE / KC
-----	-------------------------

MEDIA PLAYER COMPATIBILITY

OPS type compatible	No
---------------------	----

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
-----------------------------	---------------

Control and Monitoring Software	SuperSign Control/Control+
---------------------------------	----------------------------

ACCESSORY

Basic	Remote Controller, Power Cord, RS232C Cable, LAN Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual
-------	--

Optional	Wall Mount (Landscape: WM-L640V, Portrait: WM-P640V)
----------	--

Dimension