

<b>Printing Technology</b>	Direct Thermal
<b>Print Speed (maximum)</b>	250 mm/sec.
<b>Print Width (maximum)</b>	72 mm
<b>Media Width (min to max)</b>	59 to 80 mm (+/- 0,5 mm)
<b>Media Thickness (min to max)</b>	53 to 85 µm
<b>Media Sensor</b>	Paper end
<b>Roll Size (max), Core Size</b>	83 mm outside diameter
<b>Case</b>	Stylish flat-top case and top loading
<b>Control panel</b>	2 buttons, 2 LEDs
<b>Flash (Non-Volatile Memory)</b>	8MB
<b>Drivers and software</b>	Free-of-charge from website, including support for various platforms
<b>Size (W x D x H) and Weight</b>	125 x 170 x 108 mm. 1.26 Kg
<b>Warranty</b>	2 years including head and cutter
<b>Emulations (Languages)</b>	ESC/POS™

---

<b>Barcodes</b>	Code3of9 UPC-A UPC-E EAN-13 (JAN-13) EAN-8(JAN-8), Codabar, ITF CODE39 CODE93 CODE128 CODABAR(NW-7) PDF 417 QR Code GS1-Databar Composit Symb
<b>Media type</b>	Thermal receipt paper
<b>Cutter</b>	Guillotine type, full and partial
<b>Drawer kick-out</b>	CDK / DK connector, RJ12, 2 drawer control
<b>Power supply</b>	100 – 240V, 50-60 Hz, external power supply (supplied) or 24V DC
<b>Reliability</b>	200 Million pulses or 150 Km, 2 million cuts

---

---

<b>EMC and safety standards</b>	CE TUV UL C-UL FCC VCCI
<b>Code pages</b>	15 codepages, 17 country tables
<b>Resolution</b>	203 dpi
<b>Main Interface</b>	Dual interfaces: USB + LAN or USB + Serial
<b>Storage environment</b>	-20 to +60°C (10% to 90% RH non condensing)

---