

HP M426FDW Specs

Functions Print, scan, copy, fax

Printer

Printing Technology Laser; HP FastRes 1200, HP ProRes 1200, 600 dpi

Maximum Resolution 600 x 600 dpi (4800 x 600 enhanced dpi)

Print Speed 40 ppm

First Print Out Speed Ready: 5.4 sec
Sleep: 7.4 sec

Print Color Black

Duplex Printing Automatic

Printer Duty Cycle Monthly: 80,000 pages
Recommended Monthly Volume: 750-4,000 pages

Print Features Auto-duplex printing, N-up printing, collation, HP ePrint, Apple AirPrint, Mopria certified, Google Cloud Print, wireless direct printing, HP Auto-On/Auto-Off Technology, Print from Cloud using business apps on the control panel, HP JetAdvantage Private Print, Job Storage with PIN printing, Print from USB, JetIntelligence Cartridge Technology

Scanner

Type	Flatbed, ADF
Scan Sensor	Contact Image Sensor (CIS)
Optical Resolution	1200 x 1200 dpi
Hardware Resolution	1200 x 1200 dpi
Scan Size	ADF: 4 x 6" to 8.5 x 14.0" / 10.2 x 15.2 cm to 21.6 x 35.6 cm Flatbed: Up to 8.5 x 11.7" / 21.6 x 29.7 cm
Duplex Scanning	Automatic
Scan Speed	Black: 26 ppm / 47 ipm (duplex) Color: 21 ppm / 30 ipm (duplex)
Scan File Format	PDF, JPG
Bit Depth	24-bit
Grayscale Tones	256 levels
Scanner Features	Scan-to-E-mail; Scan-to-cloud; Scan-to-USB; Scan-to-network folder; LDAP e-mail lookup; One-pass two-sided scanning ADF

Copier

Copy Resolution	600 x 600 dpi
Copy Speed	40 cpm
Number of Copies	Up to 99 copies
Reduction/Enlargement	25-400%
Copy Features	Lighter/darker, two-sided, ID copy, optimize

Fax

Modem Speed	4.2 kbps
Transmission Speed	3 sec per page
Fax Resolution	Black (Best): 300 x 300 dpi Black (Standard): 203 x 98 dpi
Fax Memory	4 MB (250 pages)
Speed Dial Locations	120 numbers
Fax Features	Permanent fax memory backup; Auto fax reduction; Auto redialing; Delayed sending; Fax forwarding; TAM interface; Polling; Junk barrier; Distinctive ring detection; Cover page wizard; Block fax; Billing codes; Save and load; Poll receive; Fax activity reports; Dial prefix setting; Print fax log; Digital Fax Setup Wizard; Fax Setup Wizard; HP Send Fax

Media Handling

Paper Handling

Input tray 1
Input tray 2
Automatic document feeder
Output bin

Paper Types

Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough), envelopes, labels, transparencies

Paper Sizes

Input Tray 1: 3 x 5" to 8.5 x 14" / 7.6 x 12.7 cm to 21.6 x 35.6 cm
Input Tray 2: 4.1 x 5.9" to 8.5 x 14" / 10.5 x 14.9 cm to 21.6 x 35.6 cm
ADF: 4 x 6" to 8.5 x 14" / 10.2 x 15.2 cm to 21.6 x 35.6 cm

Media Weight

Tray 1: 16-47 lb
Tray 2: 16-32 lb

Paper Capacity

Input Tray 1: 100 sheets
Input Tray 2: 250 sheets
ADF: 50 sheets
Output Bin: 150 sheets

Connectivity

Interface

USB 2.0
Ethernet
Wi-Fi with NFC

USB Direct Printing

1 x Easy-access USB port

Wireless Printing Features	HP ePrint, Apple AirPrint, Google Cloud Print, Mopria-certified, wireless direct printing, NFC tap-to-print, mobile apps
OS Compatibility	Windows XP SP3 (32/64-bit), Vista (32/64-bit), 7 (32/64-bit), 8/8.1 (32/64-bit), 10 (32/64-bit) Mac OS X 10.8-10.10 iOS, Android, Windows 8/8.1/10 RT Linux OS (In-OS HPLIP) BOSS(3.0, 5.0) DEBIAN (6.0, 6.0.1, 6.0.2, 6.0.3, 6.0.4, 6.0.5, 6.0.6, 6.0.7, 6.0.8, 6.0.9, 6.0.10, 7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6) FEDORA (17, 18, 19, 20) LINUX MINT(13, 14, 15, 16, 17) SUSE LINUS (12.2, 12.3, 13.1) UBUNTU (10.04, 11.10, 12.04,12.10, 13.04, 13.10, 14.04, 14.10) MANDRIVA LINUX (2010.0, 2011.0) MEPIS (6.0, 6.5, 7.0, 8.0) PCLINUXOS (2006.0, 2006, 2007.0, 2007, 2008.0, 2008, 2009.0, 2009) RED HAT (8.0, 9.0) RED HAT ENTERPRISE LINUX (5.0, 6.0, 7.0) SLACKWARE LINUX (9.0, 9.1, 10.0, 10.1, 10.2, 11, 12, 12.1) GOS (8.04.1) IGOS(1.0) LIMPUS LINUX (9.4, 9.5) LINUX FROM SCRATCH UNIX
Processor	1.2 GHz
Memory	256 MB
Fonts	84 scalable TrueType fonts
Printer Language	HP PCL 5, HP PCL 6, HP postscript level 3 emulation, direct PDF (v 1.7) printing, URF, PCLM, PWG, Native Office

General Attributes

Control Panel 3.0" / 7.6 cm color touchscreen

Power Requirements 110-127 VAC ($\pm 10\%$), 50/60 Hz (± 2 Hz)

Power Consumption Print/Copy: 583 W
Ready: 9.1 W
Sleep: 2.7 W
Auto-On/Off: 0.7 W
Off: 0.1 W

Typical Power Consumption 1.847 kWh/week

Certifications ENERGY STAR certified
Blue Angel
EPEAT Silver

Acoustic Noise Power Emissions: 6.8 B(A)
Pressure Emissions: 55 dB(A)

Operating Conditions Temperature: 59 to 90.5°F / 15 to 33°C
Humidity: 10 to 80%, relative non-condensing
Recommended Temperature: 63.5 to 77°F / 18 to 25°C
Recommended Humidity: 30 to 70%, relative non-condensing

Storage Conditions Humidity: 10 to 90%, relative non-condensing

Dimensions 16.5 x 15.4 x 12.7" / 42.0 x 39.0 x 32.3 cm
Maximum: 16.9 x 25.0 x 12.8" / 43.0 x 63.5 x 32.5 cm

Weight

28.4 lb / 12.9 kg

Packaging Info

Package Weight

34.5 lb

Box Dimensions (LxWxH)

19 x 19 x 15"
