



Thunder 600W

RS-600-ACAB-D3



Specifications

Model	RS-600-ACAB-D3
Type	Intel ATX 12V V2.3
PFC	Active PFC (>0.9 typical)
Dimension	150 x 140 x 86mm / 5.9 x 5.5 x 3.4 inch
Input Range	180~264Vac
Input Voltage	230V Only
Input Frequency	47-63Hz
Fan Type	120mm
Efficiency	>85%@ Typical Load
MTBF	>100, 000 Hours
Protection	OVP / OCP / OPP / OTP / SCP
Operation Temp.	0~40°C
Regulatory	CE / GOST / C-tick / KC
Connectors	MB 20+4 Pin x 1 CPU12V 4+4 Pin x 1 PCI-e 6+2 Pin x 2 SATA x 6 4Pin Peripheral x 3 4Pin Floppy x 1

Features

- Compliance with Intel ATX12V V2.3
- Green power design to meet Energy Star and Blue Angel requirements
- Intelligent Fan Speed Control
- Multiple Protection Design (OVP/OCP/OPP/OTP/SCP)
- Single +12V rail provides ample power and strong resistance to any overloading
- More than 85% efficiency at typical load operation
- Huge bulk capacitor for hold-up times of >14ms when fully loaded.
- High reliability (MTBF > 100,000 hrs)

Output Rating

AC INPUT	200-240V~ 5A 47-63Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vsb
	20A	20A	47A	0.3A	2.5A
OUTPUT POWER	120W		564W	3.6W	12.5W
	600W				

Packing Information

EAN Code	4719512037737
UPC Code	884102017230
Package Information	227 x 223 x 96 mm
Carton Dimension	505 x 240 x 250 mm
Unit / Carton	5
Carton / Pallet	30
Packing Weight	2 kg / 4.4 lbs

Warranty

3 Year