



# Silent Pro Platinum 1000W

RS-A00-SPPA



The Silent Pro Platinum PSUs are fully compliant with the 80-PLUS® Platinum efficiency requirement with peak efficiency up to 94%. It features modular cable design integrated with dual 7V fan ports as well as equipped a 135mm ultra silent hydraulic bearing fan, with +12V single rail outputs efficiency that can reach up to 984W output at 82A, enough to power up most high end VGAs and CPUs at greatly quiet operation. No doubt it is specially designed for hardcore gamers who desire extremely high efficiency and powerful gaming products.

## Features

- 80 PLUS Platinum Certified: 90%, 92% and 89% Efficiency @ 20%, 50% and 100% Load
- Energy save up to 25% of energy than other power supplies
- 135 mm Ultra Silent Hydraulic Bearing Fan for lower noise and longer lifespan
- Six PCI-E 6+2 pin connectors to support high-end GPUs
- PSU integrated dual 7V fan ports adding extra cooling to your system
- Modular design incorporates a single 1000W +12V output that delivers up to 82A
- Reliable 5 year warranty

## Packaging Information

EAN Code	4719512036631
UPC Code	884102016196
Package Information	390 x 139 x 213 mm 15.35 x 5.47 x 8.38 inches
Carton Dimensions	60.6 x 33.4 x 21.8 cm 23.85 x 13.14 x 8.58 inches
Unit / Carton	4
Carton / Pallet	16

## Warranty

5 years




















## Specifications

Model Number	RS-A00-SPPA
Type	Intel Form Factor ATX 12V V2.3
Dimensions	150 x 180 x 86mm (5.9 x 7 x 3.4 inch)
Input Voltage	90-264Vac (Auto Range)
Input Current	6 - 12A
Input Frequency Range	47 - 63Hz
PFC	Active PFC (>0.95)
Power Good Signal	100-500ms
Hold Up Time	>17ms
Efficiency	92% Typically
MTBF	100,000 Hours
Protection	OVP/UVP/OCP/OPP/OTP/SCP
Output Capacity	1000W
Operation Temperature	0-40°C (Nominal Input Voltage)
Quality Certificates	TUV / CE / UL / FCC / BSMI / GOST / C-tick / KC / CCC
Fan	Silent HDB 135mm
Connectors	M/B 24 Pin Connector x 1 CPU 4+4 Pin x 2 PCI-e 6+2 Pin x 6 SATA x 12 4 Pin Peripheral x 5 4 Pin Floppy x 1 3 Pin fan Cable x 2

AC INPUT	100-240V~ 12-6A 60-50Hz					
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vsb	7V
	25A	25A	82A	0.3A	3.5A	1.5A
TOTAL POWER	150W		984W	3.6W	17.5W	10.5W
	1000W					





<p>1 x</p> <p>MB 24 pins</p> 	<p>600mm</p> 
<p>2 x</p> <p>CPU 4+4 pins</p> 	<p>650mm</p>  <p>650mm</p> 
<p>6 x</p> <p>PCI-e 6+2 pins</p> 	<p>650mm 100mm</p>  <p>650mm 100mm</p>  <p>650mm 100mm</p> 
<p>12 x</p> <p>SATA</p> 	<p>500mm 100mm 100mm 100mm</p>  <p>500mm 100mm 100mm 100mm</p>  <p>750mm 100mm 100mm 100mm</p> 
<p>5 x</p> <p>Peripherals</p>  <p>1 x</p> <p>Floppy</p>  <p>2 x</p> <p>Fan Cable 3 pin</p> 	<p>500mm 100mm 100mm</p>  <p>750mm 100mm 100mm</p>  <p>500mm</p>  <p>500mm</p> 