

HP LaserJet Enterprise M608n { Specifications }

PRINT SPEED BLACK (ISO, A4)	Normal: Up to 61 ppm [7]
FIRST PAGE OUT (READY)	Black: As fast as 5.4 sec [9]
FIRST PAGE OUT (SLEEP)	Black: As fast as 7.9 sec [9]
PRINT QUALITY BLACK (BEST)	Up to 1200 x 1200 dpi
PRINT RESOLUTION TECHNOLOGIES	FastRes 1200; 1200 x 1200 dpi
DUTY CYCLE (MONTHLY, A4)	Up to 275,000 pages Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
RECOMMENDED MONTHLY PAGE VOLUME	5000 to 25000 HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.
PROCESSOR SPEED	1.2 GHz
PRINT LANGUAGES	HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™
DISPLAY	2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle)
REPLACEMENT CARTRIDGES	HP 37A Black Original LaserJet Toner Cartridge (11,000 yield) CF237A; HP 37X High Yield Black Original LaserJet Toner Cartridge (25,000 yield) CF237X; HP 37Y Extra High Yield Black Original LaserJet Toner Cartridge (41,000 yield) CF237Y [5]
MOBILE PRINTING CAPABILITY	HP ePrint; Apple AirPrint™; Mopria-certified [6]
WIRELESS CAPABILITY	Optional, enabled with purchase of HP Jetdirect 2900nw Print Server J8031A or HP Jetdirect 3000w NFC/Wireless Accessory J8030A
CONNECTIVITY, STANDARD	1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 Host; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network; Hardware Integration Pocket
CONNECTIVITY, OPTIONAL	HP Jetdirect 2900nw Print Server J8031A; HP Jetdirect 3000w NFC/Wireless Accessory J8030A
MINIMUM SYSTEM REQUIREMENTS	2 GB available hard disk space; OS hardware requirements see microsoft.com
MINIMUM SYSTEM REQUIREMENTS FOR MACINTOSH	1.3 GB available hard drive space; Internet; OS hardware requirements see Apple.com for more info
COMPATIBLE OPERATING SYSTEMS	Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 Yosemite, OS X 10.11 El Capitan, UNIX, Windows 10 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows 7 all 32- & 64-bit

	editions, Windows 8/8.1 all 32- & 64-bit editions (excluding RT OS for Tablets)
OPERATING SYSTEM (SUPPORTED NOTE)	Full solution software available only for Windows 7 and newer, UPD software available only for Windows 7 and newer, HP Software for Mac and Windows is no longer included on the CD, but can be downloaded from 123.hp.com , Legacy Windows Operating Systems (XP, Vista, and equivalent servers) get print and Scan drivers only with a reduced feature set, Windows RT OS for Tablets (32- & 64-bit) uses a simplified HP print driver built into the RT OS
MEMORY	512 MB
MAXIMUM MEMORY	1.5 GB, MAX memory, when 1GB Accessory DIMM is installed
MEMORY FOOTNOTE	[12]
INTERNAL STORAGE	Optional, 500 GB (with accessory B5L29A)
PAPER HANDLING OUTPUT, STANDARD	500 sheet output bin
PAPER HANDLING INPUT, OPTIONAL	Optional 1x550-sheet paper feeder, optional 1x550 paper feeder and stand with cabinet, optional 3x550-sheet paper feeder and stand, optional high-capacity paper feeder and stand with 1x550 sheet feeder and 1x2,000-sheet feeder
PAPER HANDLING INPUT, STANDARD	100-sheet multipurpose feeder, 550-sheet input feeder
PAPER HANDLING OUTPUT, OPTIONAL	Optional 5 bin stapler stacker
MAXIMUM OUTPUT CAPACITY (SHEETS)	Up to 1300 sheets
DUPLEX PRINTING	Manual (driver support provided)
MEDIA SIZES SUPPORTED	feeder 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340 mm), 16K, envelopes (C5, B5, C6, DL ISO), Postcard (JIS single and double); feeder 2: A4, A5, A5-R, B5 (JIS), 16K
MEDIA SIZES, CUSTOM	feeder 1: 76 x 127 to 216 x 356 mm; feeder 2: 99 x 148 to 216 x 356 mm
MEDIA TYPES	Paper (plain, light, bond, recycled, heavy, extra heavy, cardstock, pre-printed, pre-punched, colored, rough, heavy rough), mono transparency, labels, letterhead, envelope, heavy envelope
MEDIA WEIGHT, SUPPORTED	Feeder 1: 60 to 199 g/m ² ; feeder 2: 60 to 120 g/m ²
POWER	100V - 127V nominal @ +/-10% (min 90V, max 140V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 12 A; 220V - 240V nominal, @ +/-10% (min 198V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 6 A
POWER CONSUMPTION	780 watts (printing), 15.3 watts (ready), 3.1 watts (sleep), < 0.1 watts (Auto Off/Manual On), < 0.1 watts (Manual Off) [3]
BLUE ANGEL COMPLIANT	No, please refer to the ECI (Ecolabel Comparison Information) document
OPERATING TEMPERATURE RANGE	10 to 32.5°C
RECOMMENDED OPERATING HUMIDITY RANGE	30 to 70% RH
ACOUSTIC POWER EMISSIONS (READY)	Inaudible Acoustic values are subject to change. For current information see http://www.hp.com/support . Noise measured during printing mono simplex A4 at 62ppm.
ACOUSTIC PRESSURE EMISSIONS BYSTANDER (ACTIVE, PRINTING)	55 dB(A) Acoustic values are subject to change. For current information see http://www.hp.com/support . Noise measured during printing mono simplex A4 at 62ppm.

MINIMUM DIMENSIONS (W X D X H)	431 x 466 x 380 mm
MAXIMUM DIMENSIONS (W X D X H)	431 x 1040 x 453 mm
WEIGHT	21.6 kg With print cartridges
PACKAGE DIMENSIONS (W X D X H)	597 x 497 x 539 mm
PACKAGE WEIGHT	27.2 kg
WHAT'S IN THE BOX	HP LaserJet Printer; HP Black Original LaserJet Toner Cartridge (~11K yield); CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord
WHAT IS IN THE BOX FOOTNOTE NUMBER	[2]
CABLE INCLUDED	No, please purchase (USB) cable separately
WARRANTY	1 Year Limited Warranty (Return to HP/Dealer - Standard Bench Repair)