



# Silent Pro M2 1500W

RS-F00-SPM2



Silent Pro M2 1500W features the highest wattage of our power supply series. It utilizes a powerful dual 12V rail that is capable of powering the most extreme system builds with multiple graphics cards running in NVIDIA SLI or AMD CrossFire. A skillfully designed aluminum-copper heatsink combined with a 135mm Super Silent Hydraulic Bearing fan help maintain low noise and temperatures under typical operations. A hybrid modular cable system ensures that critical components receive a strong hard wired connection while allowing the user to determine to customize their cable management. Silent Pro M2 Series features a length five year warranty.

## Features

- Quiet - 135mm Super Silent HDB Fan
- Safe - through Multiple Over Power Protections
- Powerful - Dual 12V Rail with 70A and 55A
- Smart – Modular Flat cable system
- Efficient - 80Plus Silver Certification\*
- Reliable – 5 year warranty
- Environmental Friendly - ERP & RoHS

\*varies per Model

## Specifications

Model Number	RS-F00-SPM2
Type	ATX 12V V2.3
Dimensions	150 x 220 x 86mm (5.9 x 8.6 x 3.4 inch)
Input Voltage	90-264Vac (Auto Range)
Input Current	18 - 9A
Input Frequency Range	47 - 63Hz
PFC	Active PFC (>0.9)
Power Good Signal	100-500ms
Hold Up Time	>17ms
Efficiency	88% Typically
MTBF	100,000 Hours
Protection	OVP/UVP/OC/OPP/OTP/SCP
Output Capacity	1500W
Operation Temperature	0-40°C (Nominal Input Voltage)
Quality Certificates	TUV / CE / UL / FCC / BSMI / GOST / C-tick / KC / CCC
Fan	Silent HDB 135mm
Connectors	M/B 24 Pin Connector x 1 CPU 8 Pin x 2 PCI-E 8 Pin x 6 PCI-E 6+2 Pin x 6 SATA x 12 4 Pin Peripheral x 5 4 Pin Floppy x 1

## Packaging Information















EAN Code	4719512035580
UPC Code	884102015168
Package Information	354 x 280 x 124 mm 13.9 x 11.0 x 4.8 inches
Carton Dimensions	523 x 367 x 313 mm 20.5 x 14.4 x 12.3 inches
Unit / Carton	4pcs/carton

## Warranty

5 years

AC INPUT	100-240V~ 18-9A 60-50Hz					
DC OUTPUT	+3.3V	+5V	+12V1	+12V2	-12V	+5Vsb
	30A	30A	70A	55A	0.3A	3.5A
TOTAL POWER	150W		1440W		3.6W	17.5W
	1500W					



Direct Output Cables	Modular Cables
 CPU 8 Pin 600 mm	 PCI-e 8 Pin and 6+2 Pin 650+100 mm
 CPU 8 Pin 600 mm	 PCI-e 8 Pin and 6+2 Pin 650+100 mm
 MB 24 Pin 550 mm	 PCI-e 8 Pin and 6+2 Pin 650+100 mm
 PCI-e 8 Pin and 6+2 Pin 650+100 mm	 Peripheral 4 Pin + Floppy 750+100+100 mm
 PCI-e 8 Pin and 6+2 Pin 650+100 mm	 Peripheral 4 Pin 500+100+100 mm
 PCI-e 8 Pin and 6+2 Pin 650+100 mm	 SATA 750+100+100+100 mm
	 SATA 500+100+100+100 mm
	 SATA 500+100+100+100 mm