

Behringer U-PHORIA UMC202HD - USB 2.0 Audio Interface Specs

Connectivity

Host Connection	1 x USB Type-B (USB 2.0)
Analog I/O	2 x Combo XLR-1/4" TRS Mic/Line/Hi-Z Input 2 x 1/4" TRS Monitor Output 1 x 1/4" TRS Headphone Output
Phantom Power	+48 V, Selectable On/Off (Applied to All Inputs)
Digital I/O	<i>None</i>
MIDI I/O	<i>None</i>
Memory Card Slot	<i>None</i>

Performance

Frequency Response	Mic/Line/Hi-Z Inputs: 10 Hz to 50 kHz +0/-3 dB Interface, Outputs: 10 Hz to 43 kHz +0.3 dB
Max Input Level	Mic Inputs: -4 dBu Line Inputs: +20 dBu

Hi-Z Inputs:

-3 dBu

Max Output Level

+3 dBu

Dynamic Range

110 dBA

Impedance

Mic Inputs:

3 Kilohms

Hi-Z Inputs:

1 Megohm

Digital Audio

Sample Rates

44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz

Bit Depths

24-Bit

Latency

Zero-Latency Direct Monitoring

Compatibility

OS Compatibility

macOS 10 or Later
Windows XP or Later

Power

Power Requirements

USB Bus Power

Power Consumption	2.5 W (Maximum)
-------------------	-----------------

Physical

Channels of I/O	2 Inputs / 2 Outputs
-----------------	----------------------

Max Sample Rate/Resolution	192 kHz / 24-Bit
----------------------------	------------------

Display and Indicators	2 x LED (Signal) 2 x LED (Clip) 1 x LED (+48 V) 1 x LED (Power)
------------------------	--

Anti-Theft Features	Kensington Security Slot
---------------------	--------------------------

Dimensions	7.7 x 4.9 x 1.8" / 195.58 x 124.46 x 45.72 mm
------------	---

Weight	1.2 lb / 0.5 kg
--------	-----------------

Packaging Info

Package Weight	1.845 lb
----------------	----------

Box Dimensions (LxWxH)	10.25 x 6.25 x 3.45"
------------------------	----------------------

Behringer C-1 Studio Condenser Microphone Specs

Microphone

Operating Principle	Pressure Gradient
---------------------	-------------------

Capsule	Condenser
---------	-----------

Diaphragm	0.63" / 16.0 mm
-----------	-----------------

Polar Pattern	Cardioid
---------------	----------

Performance

Frequency Range	40 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	136 dB SPL
-------------	------------

Impedance	100 Ohms
-----------	----------

Load Impedance	1000 Ohms
----------------	-----------

Sensitivity	-33 dB
-------------	--------

THD	1%
-----	----

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin
----------------------------	----------------------

Power

Operating Voltage 36 to 52 V

Operating Current Consumption 2.5 μ A

Physical

Dimensions \varnothing : 2.13 x L: 7.09" / \varnothing : 54 x L: 180 mm

Weight 0.93 lb / 0.42 kg

Packaging Info

Package Weight 1.97 lb

Box Dimensions (LxWxH) 12.05 x 5.2 x 3.4"

Behringer HPS5000 Closed-Back High-Performance Studio Headphones Specs

Headphone

Magnet Type Cobalt

Design	Over-Ear (Circumaural)
--------	------------------------

Earcup Style	Closed-Back
--------------	-------------

Connectivity

Audio Connector to Source	1 x 1/8" / 3.5 mm
---------------------------	--------------------------

Adapter (Included)	1/4"
--------------------	------

Cable

Cable Design	Single-Sided
--------------	--------------

Cable Conductor Material	Oxygen-Free Copper
--------------------------	--------------------

Physical

Packaging Info

Package Weight	0.82 lb
----------------	---------

Box Dimensions (LxWxH)	10.3 x 7.85 x 4.05"
------------------------	---------------------