

Behringer 1204USB Specs

Total # Of Inputs	12 Inputs
Mic/Line Inputs	4 x XLR Microphone Inputs 6 x 1/4" TRS Line-Level Inputs
Stereo Line Inputs	2 x 1/4" TRS Left & Right Paired Inputs
AUX Sends	2
AUX Returns	2 Stereo Returns
Inserts	None
BUS (Group) Outputs	2 Sub Groups
2 Trk Master I/O	2 x Balanced XLR Outputs
ALT I/O	2 x 1/4" TRS ALT 3 - 4 Outputs Stereo RCA 2-Track Outputs
Monitor Outputs	2 x 1/4" TRS Control Room Outputs 1 x 1/4" Stereo Headphone Output
EQ Section	3-Band EQ on Every Channel
Solo/Mute	Mute Button on Every Channel
Channel Level Control	60mm Faders

Trim/Gain Control	Yes
Phantom Power	+48 V Phantom
Metering	12-Segment Stereo LED Meters Clip LEDs on Every Channel
Frequency Response	Mic Input to Main Output:
Dynamic Range	<i>Not Specified by Manufacturer</i>
Signal-to-Noise Ratio	110 dB A-weighted (0 dBu In @ +22 dB Gain)
Total Harmonic Distortion (THD)	0.005% / 0.004% A-weighted
Power Supply	Power Consumption: 40 W Mains Voltage: 100 - 240 V, 50/60 Hz
Dimensions	3.81 x 9.72 x 12.91" (97 x 247 x 328 mm)
Weight	5.64 lb (2.56 kg)

Packaging Info

Package Weight	10.3 lb
Box Dimensions (LxWxH)	15.2 x 14.3 x 5.8"
