

Behringer MONITOR2USB Specs

Analog Inputs	2 x XLR (input set 1) 2 x XLR (input set 2)
Input Impedance	20 kOhms balanced, 10 kOhms unbalanced
Input Sensitivity	Input Set 1: +4 dBu Input Set 2: +4 dBu / -10 dBV
Analog Outputs	Monitor Out A: 2 x XLR, balanced Monitor Out B: 2 x XLR, balanced Monitor Out C: 1 x XLR, balanced Phones: 2 x 1/4" TRS, phone type
USB	USB 1.1, type-B
D/A Conversion	44.1 / 48 kHz
Frequency Response (-3 dB)	< 10 Hz to 120 kHz
SNR	85 dB at 0 dB, A-weighted
CMRR	> 50 dB at 1 kHz, 0 dBu input level, unity gain
THD+N	0.03% at 1 kHz, 0 dBu input level, unity gain
Crosstalk	> 75 dB at 1 kHz
Attenuation	Dim: -15 dB

Power Supply 100 to 240 VAC, 50 / 60 Hz

Dimensions (H x W x D) 3.3 x 8.5 x 7.8" / 84.0 x 216.0 x 199.0 mm

Weight 3.3 lb / 1.5 kg

Packaging Info

Package Weight 4.525 lb

Box Dimensions (LxWxH) 13.3 x 9.5 x 5.3"
