

Behringer DX626 Specs

Number of Channels **3 x Stereo**

EQ **Channel EQ:**
Low: -32 to +12 dB at 50 Hz
Mid: -32 to +12 dB at 1.2 kHz
Hi: -32 to +12 dB at 10 kHz
Mic EQ:
Low: ±15 dB at 80 Hz
Mid: ±15 dB at 2.5 kHz
Hi: ±15 dB at 12 kHz

Built-In Effects *None*

Connectivity

Audio Inputs **3 x Stereo RCA Unbalanced Phono Input**
3 x Stereo RCA Unbalanced Line Input
1 x XLR 3-Pin Mic Input

Audio Outputs **1 x Stereo RCA Master Output**
1 x Stereo RCA Record Output
2 x 1/4" Booth Output
1 x 1/4" TRS Headphone Output

USB *None*

Performance

Frequency Response 10 Hz to 55 kHz +0/-3 dB

SNR **Line:**
>80 dB

Power

AC Input Power 120 VAC, 60 Hz

Power Consumption 32 W

Physical

Dimensions (W x D x H) 10.0 x 12.0 x 3.6" / 254.0 x 305.0 x 91.0 mm

Weight 5.29 lb / 2.4 kg

Packaging Info

Package Weight 7.025 lb

Box Dimensions (LxWxH) 14.75 x 11.8 x 6.15"
