

# Behringer Eurorack Pro RX1602 Specs

## Audio Inputs

Type: 16 x 1/4" / 6.3 mm TRS Connectors, Electronically Balanced, Line Level  
Impedance: 20 Kiloohms Balanced or Unbalanced  
Gain Range:  $-\infty$  to +15 dB  
Operating Level: +4 dBu / -10 dBV (Switchable)  
Maximum Input Level: +22 dBu  
Common-Mode Rejection CMRR at 1 kHz: >50 dB Typically

---

## Audio Outputs

Main Out (L/R):  
Type: 2 x 1/4" / 6.3 mm TRS Connectors, Impedance Balanced  
Gain Range:  $-\infty$  to +15 dB  
Impedance: 240 Ohms Balanced, 120 Ohms Unbalanced  
Maximum Output Level: +22 dBu

Monitor Out Send (Mono):  
Type: 1 x 1/4" / 6.3 mm TRS Connector, Impedance Balanced Mono  
Impedance: 240 Ohms Balanced, 120 Ohms Unbalanced  
Maximum Output Level: +22 dBu

---

## Headphones Output

Type: 1 x 1/4" / 6.3 mm TRS Connector, Stereo  
Minimum Load Impedance: 100 Ohms

---

## System

Bandwidth: 20 Hz to 20 kHz ( $\pm 0.2$  dB)  
Frequency Range: 10 Hz to 200 kHz, ( $\pm 3$  dB)  
Signal-to-Noise Ratio: THD: 0.003% at +4 dB input, 1 kHz Unity Gain  
Crosstalk:

---

## Power Supply

Voltage: 100 to 240 VAC, 50/60 Hz  
Power Consumption: 15 W

Mains Connection: Standard IEC Connector

---

Dimensions

1.7 x 19.0 x 5.9" / 4.4 x 48.3 x 14.9 cm  
Rack Space: 1 RU

---

Weight

4.0 lb / 1.8 kg

---

## Packaging Info

---

Package Weight

5.005 lb

---

Box Dimensions (LxWxH)

20.6 x 9.8 x 4.3"

---