

Behringer Eurorack Pro RX1602 Specs

Audio Inputs

Type: 16 x 1/4" / 6.3 mm TRS Connectors, Electronically Balanced, Line Level
Impedance: 20 Kiloohms Balanced or Unbalanced
Gain Range: $-\infty$ to +15 dB
Operating Level: +4 dBu / -10 dBV (Switchable)
Maximum Input Level: +22 dBu
Common-Mode Rejection CMRR at 1 kHz: >50 dB Typically

Audio Outputs

Main Out (L/R):
Type: 2 x 1/4" / 6.3 mm TRS Connectors, Impedance Balanced
Gain Range: $-\infty$ to +15 dB
Impedance: 240 Ohms Balanced, 120 Ohms Unbalanced
Maximum Output Level: +22 dBu

Monitor Out Send (Mono):
Type: 1 x 1/4" / 6.3 mm TRS Connector, Impedance Balanced Mono
Impedance: 240 Ohms Balanced, 120 Ohms Unbalanced
Maximum Output Level: +22 dBu

Headphones Output

Type: 1 x 1/4" / 6.3 mm TRS Connector, Stereo
Minimum Load Impedance: 100 Ohms

System

Bandwidth: 20 Hz to 20 kHz (± 0.2 dB)
Frequency Range: 10 Hz to 200 kHz, (± 3 dB)
Signal-to-Noise Ratio: THD: 0.003% at +4 dB input, 1 kHz Unity Gain
Crosstalk:

Power Supply

Voltage: 100 to 240 VAC, 50/60 Hz
Power Consumption: 15 W

Mains Connection: Standard IEC Connector

Dimensions 1.7 x 19.0 x 5.9" / 4.4 x 48.3 x 14.9 cm
Rack Space: 1 RU

Weight 4.0 lb / 1.8 kg

Packaging Info

Package Weight 5.005 lb

Box Dimensions (LxWxH) 20.6 x 9.8 x 4.3"
