

Behringer UMC202HD Specs

Channels of I/O 2 Inputs / 2 Outputs

Max Sample Rate/Resolution 192 kHz / 24-Bit

Display and Indicators
2 x LED (Signal)
2 x LED (Clip)
1 x LED (+48 V)
1 x LED (Power)

Connectivity

Host Connection **1 x** USB Type-B (USB 2.0)

Analog I/O
2 x Combo XLR-1/4" TRS Mic/Line/Hi-Z Input
2 x 1/4" TRS Monitor Output
1 x 1/4" TRS Headphone Output

Phantom Power +48 V, Selectable On/Off (Applied to All Inputs)

Digital I/O *None*

MIDI I/O *None*

Memory Card Slot *None*

Performance

Frequency Response

Mic/Line/Hi-Z Inputs:
10 Hz to 50 kHz +0/-3 dB
Interface, Outputs:
10 Hz to 43 kHz +0.3 dB

Max Input Level

Mic Inputs:
-4 dBu
Line Inputs:
+20 dBu
Hi-Z Inputs:
-3 dBu

Max Output Level

+3 dBu

Dynamic Range

110 dBA

Impedance

Mic Inputs:
3 Kilohms
Hi-Z Inputs:
1 Megohm

Digital Audio

Sample Rates

44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz

Bit Depths

24-Bit

Latency

Zero-Latency Direct Monitoring

Compatibility

OS Compatibility	macOS 10 or Later Windows XP or Later
------------------	--

Power

Power Requirements	USB Bus Power
--------------------	---------------

Power Consumption	2.5 W (Maximum)
-------------------	-----------------

Physical

Anti-Theft Features	Kensington Security Slot
---------------------	--------------------------

Dimensions	7.7 x 4.9 x 1.8" / 195.58 x 124.46 x 45.72 mm
------------	---

Weight	1.2 lb / 0.5 kg
--------	-----------------

Packaging Info

Package Weight	1.845 lb
----------------	----------

Box Dimensions (LxWxH)	10.25 x 6.25 x 3.45"
------------------------	----------------------
