

# Behringer FBQ100 Specs

Frequency Response	10Hz - 21kHz
Noise	Line: > 92dB, Unweighted Mic: > 89dB, Unweighted 22Hz - 22kHz
Total Harmonic Distortion (THD)	0.007% Typical @ +4dBu, 1kHz, Gain 1
Input Level	Mic/Line Switchable +19dBu Max
Input Impedance	6 kOhms Balanced 3 kOhms Unbalanced
Output Level	Mic Level or +4dBu Switchable +20dBu @ +4dBu, -12dBu @ Mic, Max
Output Impedance	60 Ohms Balanced 30 Ohms Unbalanced
Connectors	1 x XLR Input 1 x XLR Output 1 x 1/4" TRS Input 1 x 1/4" TRS Output 1 x Power Input
Converters	24-bit Sigma-Delta, 64/128-Times Oversampling
Display	4-Digit Numeric LED Display

Power	USA/Canada: 120V~ 60Hz 19W UK/Australia: 240V~ 50Hz 20.5W Europe: 230V~ 50Hz 20W Korea: 220V~ 50Hz 20W China: 220V~ 50Hz 20W Japan: 100V~ 50/60Hz 18W
-------	--

---

Dimensions (HxWxD)	2.2 x 3.5 x 5.2" (56 x 88 x 132mm)
--------------------	------------------------------------

---

Weight	0.84 lbs (0.38kg)
--------	-------------------

---

## Packaging Info

---

Package Weight	3.055 lb
----------------	----------

---

Box Dimensions (LxWxH)	8.1 x 6.75 x 4.35"
------------------------	--------------------

---